BEVERAGE COOLER

SINGLE ZONE

Harmoniously integrate the new Presrv[™] Panel Ready Beverage Cooler into any space to match your cabinetry with ease. Featuring a Full-Extension Wood Rack to hold your favorite wine and craft brew; PreciseTemp[™] temperature control for maintaining accurate temperatures; and Active Cooling Technology to ensure even cooling.





Shown with overlay panel and handle, not included



Full-Extension Wood Rack



PreciseTemp™

How Presrv[™] Stands Out:



PreciseTemp™ Multiple internal sensors help maintain accurate temperatures



Active Cooling Technology An on-board computer controls an active cooling fan to provide temperature stability and even cooling



Vibration Dampening System Noise and vibration is reduced to minimize wine disturbance

3-Color LED Lighting Available in Cloud White, Deep Blue and Amber

Overlay Panel Dimensions



BEVERAGE COOLER

SINGLE ZONE

MODEL

Single Zone Beverage Cooler

PRB24C01BPG

13 bottles (750 ml), 84 12oz cans or

Size	24"
Dimensions	23-7/8"W x 33-7/8"H x 23-3/4"D*
Weight	110lbs.
Installation Type	Compact / Built-in / Freestanding
Refrigerant Type	R600a

FEATURES

Capacity

	7 bottles (750 ml), 112 12oz cans
Volume	5.6 cu/ft
Temperature Range	34° - 50° F
Sound Level	39 dBA
Door Finish	Panel Ready + Glass
Cabinet Finish	Black
Interior Finish	Black
Field-Reversible Door	Yes
Zero-Clearance Door Hinge	Yes
Door Glass	Dual-pane, Low-e Argon-filled**
Shelving - Wood	1 full-extension, black wood rack
Shelving - Beverage	2 adjustable, transparent-gray glass
	shelves w/ airflow openings
Controls	Electronic Capacitive Touch
Lighting	3-Color LED
	Cloud White, Deep Blue, Amber
Panel Ready	Yes, ⁵⁄ଃ" or ¾" thickness
Door Open Alarm	Yes, after 3 minutes
Sabbath Mode	Yes
Air Filtration	Yes, w/ carbon filter
PreciseTemp™	Yes
Active Cooling Technology	Yes
Vibration Dampening System	Yes

AC POWER

OPTIONAL ACCESSORIES Contemporary Handle Kit Pro Handle Kit Glass Shelf

PRHAN-C101 PRHAN-C001 50150027

WARRANTY

50150027 2 years parts, 5 years compressor 1 year labor

115V, 60Hz at Max. 1.5A

*Depth dimension based on ¾" thick panel



**Dual-pane, argon-filled glass improves insulation to minimize heat exchange and increases soundproofing characteristics. The Low-e coating helps minimize the amount of UV and infrared light that passes through the glass door.

Transforming the Kitchen through Design, Discovery, and Care

Specifications subject to change, check zephyronline.com for up-to-date information. Zephyr | 2277 Harbor Bay Parkway, Alameda, CA 94502 | 888.880.8368



*When using an optional Zephyr handle



**Depth with 3/4" thick overlay panel





