

# KPRU36X

|                    |                        |
|--------------------|------------------------|
| Product family     | Hood                   |
| Hood Type          | Integrated (semi) hood |
| Design             | Canopy pro-style       |
| Extraction         | Extraction             |
| Electronic control | Yes                    |
| Material           | Stainless steel        |
| Type of steel      | Brushed                |
| EAN code           | 8017709338572          |
| Hood width         | 36 "                   |



## Aesthetics

|           |                 |           |          |
|-----------|-----------------|-----------|----------|
| Aesthetic | Classica        | Finishing | Satin    |
| Colour    | Stainless steel | Logo      | Embossed |

## Controls



|                 |               |
|-----------------|---------------|
| Control setting | Touch control |
|-----------------|---------------|

## Programs / Functions

|                         |                                                                                     |
|-------------------------|-------------------------------------------------------------------------------------|
| No. of speeds           | 4                                                                                   |
| Intensive speed         |  |
| 24h air filter function |  |
| Auto-vent 2.0           |  |

## Technical Features



|               |       |
|---------------|-------|
| No. of lights | 2     |
| Light type    | LED   |
| Light Power   | 1.3 W |
| Dimmer mode   | Yes   |

|                              |                 |
|------------------------------|-----------------|
| No. of filters               | 2               |
| Anti-grease filters          | Stainless steel |
| Filter replacement indicator | Yes             |
| Vent outlet                  | 5 7/8 "         |






|                                    |         |                                    |       |
|------------------------------------|---------|------------------------------------|-------|
| Light color temperature scale (°K) | 3000 °K | Minimum distance from GAS hob      | 750 " |
| Free outlet maximum capacity       | 599 CFM | Minimum distance from ELECTRIC hob | 650 " |
| Motor power                        | 350 W   | Non return valve                   | Yes   |

|                 | Extraction rate IEC 61591 [CFM] | Noise level IEC 60704-2-13 [dB(A)] |
|-----------------|---------------------------------|------------------------------------|
| Speed 1         | 213                             | 54                                 |
| Speed 2         | 325.5                           | 63                                 |
| Speed 3         | 454                             | 70                                 |
| Intensive speed | 590.5                           | 76                                 |

Electrical Connection

|                              |       |                           |        |
|------------------------------|-------|---------------------------|--------|
| Electrical connection rating | 353 W | Frequency (Hz)            | 60 Hz  |
| Voltage                      | 120 V | Power supply cable length | 1000 " |



---

## Not included accessories

---



**FLTK-1**

Round Charcoal filters (kit 2 pieces)

---

## Symbols glossary (TT)

---

|                                                                                  |                                                                                                                                                           |                                                                                   |                                                                                                                                            |
|----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------|
|  | 24h: When selected this function refreshes the air for c. 10 minutes every hour over a 24 hour period, at minimum speed and an imperceptible noise level. |  | Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.                                    |
|  | Warning light(s): to advise when filters need changing.                                                                                                   |  | Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.                              |
|  | Touch controls: Easy to use touch controls allow the appliance to be programmed at the touch of a button.                                                 |  | Intensive/turbo setting: when extra fast extraction is required.                                                                           |
|  | Dimmering Lights                                                                                                                                          |  | V-Condense System is a system that avoids the drips of condensation that you could show up on the hood within certain circumstance of use. |