

Features

Channels 2	Asynchronous mode rear USB ✓	Balance / Bass / Treble / Loudness ✓ / ✓ / ✓ / ✕
Sample Rate digital In 192 kHz / 24-bit	Bit-perfect transmission ✓	Vertical installation ✓
USB-B DSD Audio Streaming (DoP): DSD2.8 / DSD5.6 ≤11.2	Ground isolator for DAC Mode operation ✓	Low Noise OELD display ✓
USB-B PCM sample rate 384 kHz / 32-bit	Bluetooth / aptX / NFC ✓ / Low Latency / ✓	Source Direct ✓

Inputs/Outputs

Audio Inputs 1	Pre-out / Main-in Subwoofer / ✕	Headphone Out ✓
Digital in: USB-B / optical / coaxial / USB-A ✓ / 2 / ✓ / ✕	Number of terminals 2	Headphone Gain Control (low / mid / high) ✓

Specifications

Output power 8 Ohm (20 Hz - 20 kHz, T.H.D. 0.07%) 25W (1kHz)	Signal to Noise Ratio: MM/MC ✕ / ✕	Treble Control = 8 dB at 12 kHz
Output power 4 Ohm (1 kHz, T.H.D. 0.7%) 50 W	Input Sensitivity: High level 70 mV	Bass Control = 8 dB at 100 Hz
Total Harmonic Distortion 0.004 %	Signal to Noise Ratio: High level 110dB	

General

Available colors: Premium Silver / Black ✓ / ✕	Auto Power Off ✓	Maximum Dimensions (W x D x H) in inches 7.87 x 9.45 x 3.39
Power Consumption in W 35	Detachable Power Cable ✓	Weight in LBS 5.75
Standby Consumption in W 0.2	Remote Control RC-1220	