

1024BEV • 24" Beverage Center • 1000 Series



STAINLESS FRAME

FEATURES & BENEFITS

PERFORMANCE

- Overall volume of 5.4 cu ft holds up to 85 bottles (12 oz) or 105 cans (12 oz) and 16 wine bottles (750 ml)
- Mechanical Dial Control is conveniently located on the grille
- Temperature range: 34°F 45°F
- Mechanical passive cooling system

INTERIOR/EXTERIOR

- White interior is illuminated with recessed incandescent lighting that automatically turns off when the door is closed
- Three-quarter extension zinc coated wine racks allow for easy access
- Wine racks accommodate a variety of bottle shapes and sizes
- Two removable tempered glass shelves
- LowE coated, argon gas filled thermopane glass door provides protection from harmful UV light
- Standard commercial stainless steel handle is interchangeable with professional handle accessory
- Door swing is field reversible

INTEGRATION

- Unit is designed to be built-in or can be freestanding with the freestanding accessory kit
- Solid natural beech wood fronts on wine racks can easily be stained to match surrounding cabinetry
- Four independently adjustable levelling legs provide a precise undercounter fit

MODEL DETAILS

| Model | Voltage | Door Swing | Finish | Shipping Weight |
|----------------|---------|-----------------------|-----------------|-----------------|
| U-1024BEVS-00A | 115 | Field Reversible Door | Stainless Frame | 126 lbs |


ACCESSORIES

| Model | Description | Finish | Shipping Weight |
|---------|---|-----------|-----------------|
| 23074 | Professional Door Handle, 1 1/4" Diameter | Stainless | 2 lbs |
| 23073 | Commercial Door Handle, 7/8" Diameter | Stainless | 2 lbs |
| U-FSK-B | Freestanding Kit | Black | 3 lbs |




1000 Series • 24" Beverage Center • 1024BEV

DIMENSIONS



CABINET CUT-OUT



INSTALLATION NOTES

When installing adjacent to wall, ensure 2 $^{1\!/\!2''}$ clearance on hinged side for 90° door opening, allowing ample room for door handle.

Cutout includes the additional 1/4" width overall to ensure proper installation.

No additional clearance around sides, top or rear of unit is needed for ventilation.

Do not obstruct front grille air flow.

SPECIFICATIONS

| Model | 1024BEV | |
|-----------------------------------|-----------------|--|
| Amps: Running | 1.2 | |
| Capacity: Bottle (12 oz) | 85 | |
| Capacity: Can (12 oz) | 105 | |
| Capacity: Volume (cu ft) | 5.4 | |
| Capacity: Wine Bottle (750 ml) | 16 | |
| Control Type | Mechanical Dial | |
| Dimensions: Product Depth | 23 ¼" / 591 mm | |
| Dimensions: Product Height | 34 ½" / 867 mm | |
| Dimensions: Product Width | 24" / 610 mm | |
| Energy Consumption: Avg. Per Year | 305 kWh | |
| ENERGY STAR | No | |
| Product Weight: Max | 116 lbs | |
| Refrigerant Type | R600a | |
| Sabbath (Star K Certified) | No | |
| Temperature Range | 34°F - 45°F | |

COOLING SYSTEM



ELECTRICAL REQUIREMENTS

This unit requires a grounded a polarized 115 VAC, 60 Hz, 15 A power supply (normal household current).



Please visit u-line.com to view this model's User Guide. All specifications are subject to change without notice.