

ELECTRICAL		
Impedance (Ω)	4	
Peak Input Power (W)	2000	
RMS Power (W)	300	
Sensitivity (dB at 1m)	85	
Frequency Response (Hz)	29 ~ 300	
MOUNTED SPEAKER		
Size	300mm	12 inch
Diaphragm	Paper	
Cap	Injection PP	
Surround	Urethane	
Basket	Steel	
Gasket	ABS	
Magnet	Ferrite	$\phi 134\text{-}\phi 70\text{-t}30$
DIMENSION		
Width	326mm	12 - 13/16 inch
Height	326mm	12 - 13/16 inch
Cut-out Diameter	279mm	11 inch
Depth	155.4mm	6 - 1/8 inch
Mounting Depth	137mm	5 - 3/8 inch
WEIGHT		
Woofer without Gasket	4.2 kg	9.3 lb
Gross Weight	5.0 kg	11.0 lb
Weight of Magnet	1560 g	54.9 oz

ELECTRICAL		
Impedance (Ω)	4	
Peak Input Power (W)	2000	
RMS Power (W)	300	
Sensitivity (dB at 1m)	85	
Frequency Response (Hz)	29 ~ 300	
MOUNTED SPEAKER		
Size	300mm	12 inch
Diaphragm	Paper	
Cap	Injection PP	
Surround	Urethane	
Basket	Steel	
Gasket	ABS	
Magnet	Ferrite	$\phi 134\text{-}\phi 70\text{-t}30$
DIMENSION		
Width	326mm	12 - 13/16 inch
Height	326mm	12 - 13/16 inch
Cut-out Diameter	279mm	11 inch
Depth	155.4mm	6 - 1/8 inch
Mounting Depth	137mm	5 - 3/8 inch
WEIGHT		
Woofer without Gasket	4.2 kg	9.3 lb
Gross Weight	5.0 kg	11.0 lb
Weight of Magnet	1560 g	54.9 oz

ELECTRICAL		
Impedance (Ω)	4	
Peak Input Power (W)	2000	
RMS Power (W)	300	
Sensitivity (dB at 1m)	85	
Frequency Response (Hz)	29 ~ 300	
MOUNTED SPEAKER		
Size	300mm	12 inch
Diaphragm	Paper	
Cap	Injection PP	
Surround	Urethane	
Basket	Steel	
Gasket	ABS	
Magnet	Ferrite	$\phi 134\text{-}\phi 70\text{-t}30$
DIMENSION		
Width	326mm	12 - 13/16 inch
Height	326mm	12 - 13/16 inch
Cut-out Diameter	279mm	11 inch
Depth	155.4mm	6 - 1/8 inch
Mounting Depth	137mm	5 - 3/8 inch
WEIGHT		
Woofer without Gasket	4.2 kg	9.3 lb
Gross Weight	5.0 kg	11.0 lb
Weight of Magnet	1560 g	54.9 oz

ELECTRICAL		
Impedance (Ω)	4	
Peak Input Power (W)	2000	
RMS Power (W)	300	
Sensitivity (dB at 1m)	85	
Frequency Response (Hz)	29 ~ 300	
MOUNTED SPEAKER		
Size	300mm	12 inch
Diaphragm	Paper	
Cap	Injection PP	
Surround	Urethane	
Basket	Steel	
Gasket	ABS	
Magnet	Ferrite	$\phi 134\text{-}\phi 70\text{-t}30$
DIMENSION		
Width	326mm	12 - 13/16 inch
Height	326mm	12 - 13/16 inch
Cut-out Diameter	279mm	11 inch
Depth	155.4mm	6 - 1/8 inch
Mounting Depth	137mm	5 - 3/8 inch
WEIGHT		
Woofer without Gasket	4.2 kg	9.3 lb
Gross Weight	5.0 kg	11.0 lb
Weight of Magnet	1560 g	54.9 oz

ELECTRICAL		
Impedance (Ω)	4	
Peak Input Power (W)	2000	
RMS Power (W)	300	
Sensitivity (dB at 1m)	85	
Frequency Response (Hz)	29 ~ 300	
MOUNTED SPEAKER		
Size	300mm	12 inch
Diaphragm	Paper	
Cap	Injection PP	
Surround	Urethane	
Basket	Steel	
Gasket	ABS	
Magnet	Ferrite	$\phi 134\text{-}\phi 70\text{-t}30$
DIMENSION		
Width	326mm	12 - 13/16 inch
Height	326mm	12 - 13/16 inch
Cut-out Diameter	279mm	11 inch
Depth	155.4mm	6 - 1/8 inch
Mounting Depth	137mm	5 - 3/8 inch
WEIGHT		
Woofer without Gasket	4.2 kg	9.3 lb
Gross Weight	5.0 kg	11.0 lb
Weight of Magnet	1560 g	54.9 oz