# SC(B)513 | ALITO Collection







### **Wall Mount**

The SC(B)513 features three filters across the bottom of the fan, two bright LED lights, a digital control panel, and a straight-edged stainless steel frame. This is a quality fan for cooks who demand performance. Option to upgrade to baffle filters available. Fitted with a time-delay OFF feature of up to nine minutes.

#### **Green Features**



3 Speed Push Button Control Panel



Long-Lasting LED Lights



Time-Delay OFF Feature



Grease Cup


| Model    | Colour          | Ducting | Filters | Size | CFM |
|----------|-----------------|---------|---------|------|-----|
| SC51330  | Stainless Steel | 6"      | Mesh    | 30"  | 550 |
| SC51336  | Stainless Steel | 6"      | Mesh    | 36"  | 550 |
| SCB51330 | Stainless Steel | 6"      | Baffle  | 30"  | 550 |
| SCB51336 | Stainless Steel | 6"      | Baffle  | 36"  | 550 |


# SC(B)513 | ALITO Collection



#### **Features**

- · Wall mount range hood
- 6" round duct adapter
- · Non-stick aluminum fan blades
- · 3 speed push button control
- 2 LED lights (2 x 1.4W, 4000K)
- · Quick release aluminum mesh filters
- · Standard chimney fits up to 9 ft. ceiling
- Up to 9 minutes time-delay OFF feature
- Plug-in connection





## **Options**

Filters:

SC513 - Quick Release Aluminum Mesh Filters SCB513 - Quick Release Stainless Steel Baffle Filters

Chimney Flues:

B2.CH16 - short (7'-8' ceilings)

B2.CH22 - standard (8'-9' ceilings)

B2.CH32 - extended (9'-11' ceilings)

• Widths: 30", 36"

### **Specifications**

Air Flow Volume: 550 CFM

Electrical Connection: 120 V/60 Hz

Power Consumption: 300 Watts

Current: 2.5 Amps

Fan Speed: 1599 RPM

Fan Type: Centrifugal Blower

· Finishes: Stainless Steel

- Ducting: 6" Round

Noise Level: Min. 2 Sones
Max. 6 Sones

