

	S/N (dB)	50dB (MONO)
	Selectivity	-
	Stereo separation	35dB (1kHz)
AM	Frequency Range	530 - 1700 kHz
	(Frequency step)	(10kHz)
	Usable sensitivity	99 μ V(40dB μ)
Video	Color system of external video input	NTSC/ PAL
	External video input level (Mini jacks)	1.0Vp-p / 75 Ohms
	External audio max input level (RCA jacks)	1.5V / 25k Ohms
	Video Output level (RCA jacks)	1.0Vp-p / 75 Ohms
Audio	Maximum Power Output (Front&Rear)	45Wx4
	Full Bandwidth Power	21Wx4
	(at less than 1%THD)	
	Output frequency band	20 - 20,000Hz
	Preout level (V)	2.0V / 10k Ohms
	Preout impedance (Ω)	1.4k Ohms
	Speaker Impedance (Ω)	4-8 Ohms
General	Operating voltage	12V DC Car Battery
	Installation Dimensions WxHxD	182 x 112 x 75 (mm)
		7-3/16 x 4-7/16 x 2-15/16 (inch)
	Main Unit Installation size W x H x D(w/o sleeve)	178 x 100 x 75 (mm)
		7 x 3-15/16 x 2-15/16 (inch)
	Weight Main unit	1.1 kg / 2.4 lbs
	(Including Sleeve and Trim plate)	1.3 kg / 2.8 lbs

	S/N (dB)	50dB (MONO)	ecs
	Selectivity	-	
	Stereo separation	35dB (1kHz)	sic,
AM	Frequency Range	530 - 1700 kHz	rol.
	(Frequency step)	(10kHz)	+
	Usable sensitivity	99μV(40dBμ)	
Video	Color system of external video input	NTSC/ PAL	
	External video input level (Mini jacks)	1.0Vp-p / 75 Ohms	
	External audio max input level (RCA jacks)	1.5V / 25k Ohms	
	Video Output level (RCA jacks)	1.0Vp-p / 75 Ohms	
Audio	Maximum Power Output (Front&Rear)	45Wx4	
	Full Bandwidth Power	21Wx4	
	(at less than 1%THD)		
	Output frequency band	20 - 20,000Hz	
	Preout level (V)	2.0V / 10k Ohms	
	Preout impedance (Ω)	1.4k Ohms	
	Speaker Impedance (Ω)	4-8 Ohms	
General	Operating voltage	12V DC Car Battery	
	Installation Dimensions WxHxD	182 x 112 x 75 (mm)	
		7-3/16 x 4-7/16 x 2-15/16 (inch)	
	Main Unit Installation size W x H x D(w/o sleeve)	178 x 100 x 75 (mm)	
		7 x 3-15/16 x 2-15/16 (inch)	
	Weight Main unit	1.1 kg / 2.4 lbs	
	(Including Sleeve and Trim plate)	1.3 kg / 2.8 lbs	

	S/N (dB)	50dB (MONO)
	Selectivity	-
	Stereo separation	35dB (1kHz)
AM	Frequency Range	530 - 1700 kHz
	(Frequency step)	(10kHz)
	Usable sensitivity	99 μ V(40dB μ)
Video	Color system of external video input	NTSC/ PAL
	External video input level (Mini jacks)	1.0Vp-p / 75 Ohms
	External audio max input level (RCA jacks)	1.5V / 25k Ohms
	Video Output level (RCA jacks)	1.0Vp-p / 75 Ohms
Audio	Maximum Power Output (Front&Rear)	45Wx4
	Full Bandwidth Power	21Wx4
	(at less than 1%THD)	
	Output frequency band	20 - 20,000Hz
	Preout level (V)	2.0V / 10k Ohms
	Preout impedance (Ω)	1.4k Ohms
	Speaker Impedance (Ω)	4-8 Ohms
General	Operating voltage	12V DC Car Battery
	Installation Dimensions WxHxD	182 x 112 x 75 (mm)
		7-3/16 x 4-7/16 x 2-15/16 (inch)
	Main Unit Installation size W x H x D(w/o sleeve)	178 x 100 x 75 (mm)
		7 x 3-15/16 x 2-15/16 (inch)
	Weight Main unit	1.1 kg / 2.4 lbs
	(Including Sleeve and Trim plate)	1.3 kg / 2.8 lbs

	S/N (dB)	50dB (MONO)	ecs
	Selectivity	-	
	Stereo separation	35dB (1kHz)	
AM	Frequency Range	530 - 1700 kHz	
	(Frequency step)	(10kHz)	
	Usable sensitivity	99μV(40dBμ)	
Video	Color system of external video input	NTSC/ PAL	
	External video input level (Mini jacks)	1.0Vp-p / 75 Ohms	
	External audio max input level (RCA jacks)	1.5V / 25k Ohms	
	Video Output level (RCA jacks)	1.0Vp-p / 75 Ohms	
Audio	Maximum Power Output (Front&Rear)	45Wx4	
	Full Bandwidth Power	21Wx4	
	(at less than 1%THD)		
	Output frequency band	20 - 20,000Hz	
	Preout level (V)	2.0V / 10k Ohms	
	Preout impedance (Ω)	1.4k Ohms	
	Speaker Impedance (Ω)	4-8 Ohms	
General	Operating voltage	12V DC Car Battery	
	Installation Dimensions WxHxD	182 x 112 x 75 (mm)	
		7-3/16 x 4-7/16 x 2-15/16 (inch)	
	Main Unit Installation size W x H x D(w/o sleeve)	178 x 100 x 75 (mm)	
		7 x 3-15/16 x 2-15/16 (inch)	
	Weight Main unit	1.1 kg / 2.4 lbs	at
	(Including Sleeve and Trim plate)	1.3 kg / 2.8 lbs	OT

	S/N (dB)	50dB (MONO)	ecs
	Selectivity	-	
	Stereo separation	35dB (1kHz)	
AM	Frequency Range	530 - 1700 kHz	
	(Frequency step)	(10kHz)	
	Usable sensitivity	99μV(40dBμ)	
Video	Color system of external video input	NTSC/ PAL	
	External video input level (Mini jacks)	1.0Vp-p / 75 Ohms	
	External audio max input level (RCA jacks)	1.5V / 25k Ohms	
	Video Output level (RCA jacks)	1.0Vp-p / 75 Ohms	
Audio	Maximum Power Output (Front&Rear)	45Wx4	
	Full Bandwidth Power	21Wx4	
	(at less than 1%THD)		
	Output frequency band	20 - 20,000Hz	
	Preout level (V)	2.0V / 10k Ohms	
	Preout impedance (Ω)	1.4k Ohms	
	Speaker Impedance (Ω)	4-8 Ohms	
General	Operating voltage	12V DC Car Battery	
	Installation Dimensions WxHxD	182 x 112 x 75 (mm)	
		7-3/16 x 4-7/16 x 2-15/16 (inch)	
	Main Unit Installation size W x H x D(w/o sleeve)	178 x 100 x 75 (mm)	
		7 x 3-15/16 x 2-15/16 (inch)	
	Weight Main unit	1.1 kg / 2.4 lbs	
	(Including Sleeve and Trim plate)	1.3 kg / 2.8 lbs	

	S/N (dB)	50dB (MONO)	ecs
	Selectivity	-	
	Stereo separation	35dB (1kHz)	
AM	Frequency Range	530 - 1700 kHz	
	(Frequency step)	(10kHz)	
	Usable sensitivity	99μV(40dBμ)	
Video	Color system of external video input	NTSC/ PAL	
	External video input level (Mini jacks)	1.0Vp-p / 75 Ohms	
	External audio max input level (RCA jacks)	1.5V / 25k Ohms	
	Video Output level (RCA jacks)	1.0Vp-p / 75 Ohms	
Audio	Maximum Power Output (Front&Rear)	45Wx4	
	Full Bandwidth Power	21Wx4	
	(at less than 1%THD)		
	Output frequency band	20 - 20,000Hz	
	Preout level (V)	2.0V / 10k Ohms	
	Preout impedance (Ω)	1.4k Ohms	
	Speaker Impedance (Ω)	4-8 Ohms	
General	Operating voltage	12V DC Car Battery	
	Installation Dimensions WxHxD	182 x 112 x 75 (mm)	
		7-3/16 x 4-7/16 x 2-15/16 (inch)	
	Main Unit Installation size W x H x D(w/o sleeve)	178 x 100 x 75 (mm)	
		7 x 3-15/16 x 2-15/16 (inch)	
	Weight Main unit	1.1 kg / 2.4 lbs	
	(Including Sleeve and Trim plate)	1.3 kg / 2.8 lbs	