

## DAS 8930

### Built-in ventilation hood

with intuitive SmartControl White controls for use in narrow upper cabinets



- Intricate design – flat stainless-steel panel, 36 in (90 cm) wide
- Unique user convenience – Con@ctivity
- LED strip for uniform lighting
- Efficient filtration- 10-ply stainless steel grease filters
- Recirculation mode – Active AirClean or Longlife AirClean filter

EAN: 4002516495628 / Material number: 11878590 / Old Material Number: 28S8930SUSA

<b>Construction type</b>	
Built-in ventilation hood	•
<b>Operating modes</b>	
Recirculated mode	Convertible
Recirculation conversion kit (order separately)	DUU 151
<b>Design</b>	
Color	Stainless steel
<b>Control panel</b>	
Miele@home	•
Automatic function Con@ctivity 3.0 (WiFi)	•
Electronic controls	•
Touch controls on glass	•
Programmable Intensive switch-off	•
Delayed shutdown for 5 or 15 minutes	•
Grease filter saturation indicator	•
Programmable grease filter saturation indicator	•
Programmable charcoal filter saturation indicator	•
<b>Cleaning convenience</b>	
Easy to clean canopy interior CleanCover	•
<b>Filter system</b>	
Number of dishwasher-safe stainless-steel grease filters	2
<b>Lighting</b>	
LED	•
Number x W	1 x 3 W
Light intensity in lx	270 lx
Color temperature in K	3500 Kelvin
Light dimmer function	•
<b>Blower</b>	
Dual-action blower	•
AC motor	•
<b>Safety</b>	
Safety shut-off	•
<b>Technical data</b>	
Canopy width in in.(mm)	34 (861)
Canopy height in in.(mm)	2 3/8 (60)
Canopy depth in in.(mm)	12 1/8 (307)
Net weight in lbs. (kg)	42 (19.0)
Length of electrical wire in ft (m)	2 (0.8)
Standard plug fitted	•
Minimum distance above electric cooktops in in. (mm)	24 1/8 (610)
Minimum height above gas cooktop (max. 12.6 kW total power, burner ≤ 4.5 kW) in mm	26 (660)
Total connected load in kW	0.35
Voltage in V	120
Fuse rating in A	15
Number of phases	1
Frequency in Hz	60
<b>Installation notes</b>	
Vent connection at top	•
Vent connection at top and rear	•

DAS 8930

Built-in ventilation hood

with intuitive SmartControl White controls for use in narrow upper cabinets



EAN: 4002516495628 / Material number: 11878590 / Old Material Number: 28S8930SUSA

Installation template

•

**Accessories supplied**

Non-return flap

•

**Optional accessories**



OdorFree charcoal filter

Nein

## DAS 8930



### Built-in ventilation hood

with intuitive SmartControl White controls for use in narrow upper cabinets



DAS8930, Installation drawings

1) Extraction, recirculation with conversion kit DUU 150.,  
 2) Alternative ducting connection to the rear., 3) Accessory DSM module., 4) The wall unit can be fitted with a partition after installation. The slots for the grease filters and, in recirculation mode, for the odor filters must remain accessible., , The height of the wall unit and the cut-out dimensions must take into account any accessories fitted (e.g. silencer, recirculation hood conversion kit, DSM module)



DAS8930, drawing – US

1) Exhaust air, recirculation with DUU 150 conversion kit.,  
 2) Exhaust air connection alternatively to the rear., 3) DSM module accessory., 4) The wall unit can be fitted with a partition after installation. The slots for the grease filters and, in the case of recirculation mode, for the odor filters must remain accessible., , Mounted accessories must be taken into account for the cabinet height and cut-out dimensions (e.g. silencer, recirculation air conversion kit, DSM module).