Specifications

Standards and Protocol			IEEE 802.3：10BASE-T IEEE 802.3 u：100BASE-X IEEE 802.3 z：1000BASE-T IEEE 802.3 ab：1000BASE-T IEEE 802.3 ae：10G BASE-SR/LR IEEE 802.3 bz：2.5G/5G BASE-T IEEE 802.3 cb：2500BASE-X
Ports	SS-1 Pro		2x 100Mbps/10Mbps RJ45 6x 2.5Gbps/1Gbps/100Mbps/10Mbps RJ45 2x 10Gbps SFP/SFP+
	SS-1		2x 100Mbps/10Mbps RJ45 4x 2.5Gbps/1Gbps/100Mbps/10Mbps RJ45 2x 10Gbps SFP/SFP+
External Clock Input	Exclusive on SS-1 Pro		10MHz / 50Ω impedance / Sine wave or square wave input
LED Indicators			1x LED - Power/Status 2x LED - Clock mode (SS-1 Pro only) Each LAN Port has 2 LEDs - Speed, Link & Activity
Max MAC entries			16K MAC address table
Power Specs	SS-1 Pro		AC input Power Supply Type: Auto voltage range linear power supply Power Voltage: AC 100V-120V 50/60Hz / AC 220V-240V 50/60Hz. Voltage auto adaptive. Power Consumption: < 15W
	SS-1		AC input Power Supply Type： Wide voltage input switching power supply Power Voltage: AC 100V-240V 50/60Hz Power Consumption: < 15W
			DC input External power voltage: DC 12V ±10% External power wattage: Larger than 18W Power plug: Outer diameter 5.5mm; inner diameter 2.1mm (+ for inner, - for outer)
Weight & size	SS-1 Pro	Weight	3.4kg (7.50 pounds)
		Dimensions	Width: 330 mm (12.99 inches) Depth: 235 mm (9.25 inches) Height: 58.5 mm (2.30 inches)
	SS-1	Weight	2.3kg (5.07 pounds)
		Dimensions	Width: 280 mm (11.02 inches) Depth: 206 mm (8.11 inches) Height: 58.5 mm (2.30 inches)
Accessories			Power cable *1

Quick start guide *1

Warranty card *1