assembly instructions



bdiusa.com customerservice@bdiusa.com

Placement and Maintenance

Sequel[™] Home Office Furniture is designed for indoor use on level floors. Clean glass with glass cleaner, and steel parts and wood veneer with a moist cloth. Your Sequel[™] Home Office Furniture is engineered for easy assembly. Carefully follow this procedure to prevent any damage.

Do not use power tools for assembly of this product.

Step 1

Made in Taiwan. 6001REV082115v10

Unpack and identify the parts listed below. The assembly workspace should be a nonmarring surface such as carpet. For missing hardware pieces, please contact BDI Customer Service at customerservice@bdiusa.com. For all other concerns, please contact your BDI Retailer.







Step 1 Install Glides (M) to the bottom of Left Leg (K) and Right Leg (L).







Step 2 Attach Left Leg (K) to Drawer Assembly (A) using Screw (H) and Hex Wrench (F).









Step 3

Step 4

Attach **Upper Horizontal Beam (N)** to inside of Left and Right Leg using **Screw (H)** and **Hex Wrench (F)**.







Step 5 Attach Lower Horizontal Beam (E) to inside of Left and Right Leg using Screw (H) and Hex Wrench (F).











Step 6

With the help of another person, gently lower Assembly onto **Top Glass (B)**. Both parts will be placed upside down for the assembly process and fasten into place using **Screw (G)** and **Hex Wrench (F)** at all **(7)** fastener locations. **DO NOT OVERTIGHTEN!** With the help of another person, turn desk upright onto its base.



2 Person Task





Step 7 (optional) Attach Magnets to AC power strip/surge protector Remove Adhesive Foam/Magnets (I) from the Upper Horizontal Beam (N). Peel film from side of the Adhesive Foam/Magnets (I) and attach to clean, dry back side of AC power strip (not included). Cleaning of power strip surface with rubbing alcohol will ensure best adhesive bond. **UNPLUG POWER STRIP FROM

POWER SOURCE BEFORE CLEANING**

Attach AC power strip/surge protector to inside of **Upper Horizontal Beam (N)** as shown in illustration above.

Use the slot holes provided to run all wires to and from the desk. Keep all wires behind folded metal lip-failure to do so will prevent **Back Panel (C)** 1. and/or Front Kick Panel (D) from attaching properly. 3. 2. 4. Ν ('.') œ





Step 11

Place Sequel Desk in desired location. Once all of the electrical wires are routed, install **Kick Panel (D)** as shown above. The rear side of panel has magnets that will hold the panel in place. **Note:** The Sequel Desk is designed to permit placement in front of an electrical outlet for easier wiring access.



Optional Step

The **Back Panel (C)** is provided to conceal wire management, if desk is located in the middle of a room.

