KLIPSCH PIC-525-T-SC

5.25" SHORT-CAN
PROFESSIONAL IN-CEILING SPEAKER



MORE BASS, LESS SPACE WITH THE ALL-NEW TRACTRIX® HYPERFOLD PORT™
Klipsch is all about high efficiency, low distortion. Building upon that legacy, we're introducing the all-new patented Tractrix® Hyperfold Port™ engineered to extend port length for maximum bass power via proprietary five-step folded design. Its increased airflow eliminates chuffing and port noise while providing a greater dispersion pattern for larger coverage areas, especially in this short can model.

EXCLUSIVE PATENTED SKY HOOK® PRO SYSTEM FOR FASTER, TOOL-FREE INSTALLATION
The Klipsch PIC-525-T-SC was engineered for once the hole is cut. After that, this tool-free installation is a breeze with the exclusive patented Sky Hook® Pro. Utilizing this new technology means you no longer need to worry if the screw gun is set to the correct torque (if you're even using one). A simple click of four buttons and the PIC-525-T-SC is installed.

IPX5 RATED FOR CHALLENGING COMMERCIAL ENVIRONMENTS
Perfect for commercial projects around the globe, the Klipsch PIC-525-T-SC is IPX5 Rated. Your clients will rest easy knowing their new speakers will have maximum weather resistance for even the most challenging environments.

1" TITANIUM COMPRESSION DRIVER FOR EFFORTLESS, HIGH-CLARITY DETAIL
Klipsch outperforms the competition with our all-new 1" Titanium-loaded floating driver bridge with wide dispersion phase plug. Using our patented mumps technology, the PIC-525-T-SC gives any space extra-wide coverage while providing even and consistent energy for your project.

BLACK AND WHITE PAINTABLE GRILLE OPTIONS INCLUDED
Meant to fit into any space, the Klipsch PIC-525-T-SC comes with both a black and white grille in the box.

PHOENIX CONNECTOR FOR SIMPLIFIED INSTALLATION
The PIC-525-T-SC employ a phoenix connector for quick and intuitive connection.

SPECIFICATIONS

FREQUENCY RESPONSE[1]	95Hz-20kHz +/- 4dB, 60Hz -10dB
POWER HANDLING[2]	65 watts (16.7V) 55Hz-10kHz (260 watts peak)
CALC. MAX. CONT. OUTPUT[3]	104dB
SENSITIVITY[4]	89dB
COVERAGE	100° +/- 20° 1kHz-20kHz
DIRECTIVITY INDEX	7dB +/- 1.5dB 1kHz-20kHz
NOMINAL IMPEDANCE	8 ohms 4.3 ohms at 175Hz minimum
ACOUSTIC CROSSOVER	2kHz
TRANSDUCERS	5.25" woofer 1" titanium compression driver, on a K-1200M Tractrix horn/tweeter bridge
ENCLOSURE MATERIAL	All Weather Abs Plastic, Paintable; Metal Can
ENCLOSURE TUNING	Vented via 3 folded Tractrix ports
INPUT CONNECTORS	4 pin euro block
TRANSFORMER TAPS	70V: 30W, 15W, 7.5W, 3.8W 100V: 30W, 7.5W, 3.8W Bypass position: 8ohms nominal
UL RATING	UL2043, 1480A
CUTOUT DIMENSION	10.125"
MOUNTING DEPTH	3.875"
OVERALL DEPTH	4.438"
OVERALL WIDTH	11.25"
THRU HOLE WIDTH	10"
WEIGHT	8 lbs

FOR LIT POLARS CLICK HERE

[1] 1m, half space, anechoic
[2] AES standard, continuous pink noise, 6db peaks
[3] Calculated at 1m at power handling power input
[4] SPL at 1m half space, anechoic with 2.83v pink noise input

All specifications are subject to change without notice. ©2023 Premium Audio Company, LLC, a wholly-owned subsidiary of Voxx International Corporation. Klipsch Group, Inc. is a wholly owned subsidiary of Voxx International Corporation. Klipsch is a trademark registered in the USA and other countries, and is owned by Klipsch Group, Inc.