

General Specifications

Seven channels driven, 4Ω / 8Ω, 20Hz – 20kHz: 140W / 100W

Five channels driven, 4Ω / 8Ω, 1kHz: 175W / 110W

Two channels driven, 4Ω / 8Ω, 1kHz: 225W / 140W

Harmonic distortion, 80% power, 8Ω at 1kHz: 0.002%

Input sensitivity 50W / 8Ω: 800mV RMS (RCA Type), 1.6V RMS (XLR Type)

Signal/Noise ratio (A-wtd) 50W / 8Ω: 105dB

Input impedance: 10kΩ

Frequency response: 20 - 20kHz +/-0.05dB

Mains voltage: 110–120V or 220–240V, 50–60Hz

Maximum power consumption: 1.5kW

Dimensions W x H x D (including feet, control knob and speaker terminals): 433 x 425 x 177mm

Weight (net): 18kg

Weight (gross): 19.7kg

Audio Specifications

Seven channels driven, 4Ω / 8Ω, 20Hz – 20kHz	140W / 100W
Five channels driven, 4Ω / 8Ω, 1kHz	175W / 110W
Two channels driven, 4Ω / 8Ω, 1kHz	225W / 140W
Harmonic distortion, 80% power, 8Ω at 1kHz	0.002%
Input sensitivity 50W / 8Ω	800mV RMS (RCA Type), 1.6V RMS (XLR Type)
Signal/Noise ratio (A-wtd) 50W / 8Ω	105dB
Input impedance	10kΩ
Frequency response	20 - 20kHz +/-0.05dB
Mains voltage	110–120V or 220–240V, 50–60Hz
Maximum power consumption	1.5kW
Dimensions W x H x D (including feet, control knob and speaker terminals)	433 x 425 x 177mm
Weight (net)	18kg
Weight (gross)	19.7kg