

UP60N



Colour range

Body



Blue
grey – BG



Antique
white – AW



White – WH



Blue – MB



Stainless
steel – SS



Graphite
matt – MG



Glossy
black – BK



Burgundy
red – BU



Emerald
green – EG



Optional RAL – RA

Finishes

Knobs, handles, frames (optional)



Brass – G



Copper – P



Chrome – C



Burnished – B

Optional solid door version

Order code: add letter "Q" before the "N" letter



Noblesse frames

optional → p. 138

Available ovens

Electric oven	
Primary oven:	Secondary oven:
UOV 80 M	UOV 60 M
Maximum input:	Maximum input:
3.7 kW	3.5 kW

Configurations

7 burners with fry top* and coup de feu	9 burners with fry top*
	

Electric oven


UP60FSNMP	UP60FNMP
Brass/Copper/Chrome/Burnished	Brass/Copper/Chrome/Burnished

Fuel requirements

Natural gas / Liquid propane	Natural gas / Liquid propane
Voltage: 240 Volts	Voltage: 240 Volts
Amps: 30	Amps: 30

**Insufficient amperage may lower heating performance when multiple functions are being used at the same time*

Consumption

 Coupe de Feu 5500 btu/h	 Double ring Dual burner 25000 btu/h / 900 btu/h	 Griddle 10500 btu/h / 2000 btu/h + 7000 btu/h / 1400 btu/h	 Oval burner 10500 btu/h / 3100 btu/h	 Big burner 10500 btu/h / 2000 btu/h	 Small burner 7000 btu/h / 1400 btu/h
---	--	--	--	---	--

Complements & accessories

Hood	UAG60	Hood	UANB60	Ladle holder panel	AM4-150
		Brass/Copper/Chrome/Burnished			

Technical drawing & dimensions

