

HA-L7A Specifications		
Frequency response (HP OUT)		4 Hz - 80 KHz, -3 dB
Headphone Output	6.3mm	1,000 mW + 1,000 mW (1 kHz, 0.01 %THD, 32 Ω)
	4.4mm	1,000 mW + 1,000 mW (1 kHz, 0.01 %THD, 32 Ω)
	XLR4	1,000 mW + 1,000 mW (1 kHz, 0.01 %THD, 32 Ω)
Total Harmonic Distortion(THD)		≤ 0.003 % (Digital IN 1 kHz, 300 mW, 32 Ω)
Signal to Noise Ratio (SNR)		> 120 dB
Input	RCA	Yes
	Optical	Yes (PCM: 32/44.1/48/88.2/96 kHz, 16/24 bit)
	Coaxial	Yes (PCM: 32/44.1/48/88.2/96/176.4/192 kHz, 16/24 bit)
	USB Type-B	Yes (PCM: 44.1/48/88.2/96/176.4/192/352.8/384 kHz, 16/24/32 bit, DSD: 2.8 MHz/5.6 MHz/11.2 MHz: ASIO Native, DoP)
PRE/LINE Out	XLR3	Yes
	RCA	Yes
Recommended Headphones impedance		32 ~ 600 Ω
SOUND FIELD mode		Yes (CINEMA/DRAMA/MUSIC VIDEO/CONCERT HALL/OUTDOOR LIVE/BGM + STRAIGHT)
Pure Direct		Yes
Power Consumption		19 W
Standby Power Consumption		0.2 W
Dimensions (W x H x D)		333 x 133 x 189 mm; 13 1/8" x 5 1/4" x 7 1/2" (w/ Trans, Leg, knob, terminal)
Weight		5.3 kg, 11.7 lbs