


SPECIFICATIONS

FREQUENCY RESPONSE	37Hz - 26kHz
SENSITIVITY	90dB (2.83V @ 1m)
POWER HANDLING (CONT/PEAK)	120W / 240W
NOMINAL IMPEDANCE	8 Ohm
HIGH FREQUENCY DRIVER	25mm (1") Soft Dome Tweeter
LOW FREQUENCY DRIVER	3 x 127mm (5") Polyfiber Woofers
ENCLOSURE MATERIAL	MDF
ENCLOSURE TYPE	Bass Reflex via Front Firing Slot Port
INPUTS	Single Binding Posts (Main / Height)
FINISHES	Black, Walnut, White (Shown)
DIMENSIONS (HxWxD)	1042mm x 191mm x 252mm 8 70" x 6 5" x 10 25"



S 809

COMPLETELY NEW, COMPLETELY MODERN

The new Jamo Studio 8 series has been completely reimagined to live seamlessly in modern, premium environments. Contemporary material and finish choices accentuate the clean, minimalist lines of this European design, while the compact cabinet designs are an ideal solution for urban living environments around the world.

PREMIUM PERFORMANCE

The 1" soft dome tweeter provides smooth, refined high frequencies, with three 5" polyfiber woofers for balanced, cinematic low end. The integrated WaveGuide focuses the high frequency sound for dynamic, true-to-life reproduction, while the front-firing tube port allows for better low frequency extension with placement flexibility.

SEAMLESS DOLBY ATMOS® INTEGRATION

Elegant metal fasteners atop the cabinet provide a chic, modern industrial look, but also serve as a connection point for the S 8 ATM Dolby Atmos elevation speaker. This patentpending design allows for all of the wire connections on the back of the floorstander, avoiding unsightly and messy speaker wire going all the way up to the Atmos module -

for cinematic, completely immersive Dolby Atmos® sound while preserving the beautiful aesthetic of the Jamo Studio 8 Series.



