Product data sheet

•
36
•
Natural gas
Stainless steel/Clean Steel
M Touch
OVEN
•
•
•
•
•

Broil	•	
Intensive	•	
Moisture Plus	•	
Slow Roasting	•	
Surround	•	
Browning	•	
Bake	•	
Convection Broil	•	
Special modes	•	
Convection Bake	•	
Convection Roast	•	

COOKTOP FEATURES

Number of gas burners	4
Number and power rating of griddle surfaces in BTU/h	1 x 13.000
Number and power rating of gas burners in BTU/h	2 x 19.500
Number and power rating of gas burners in BTU/h	1 x 13.600
Number and power rating of gas burners in BTU/h	1 x 12.500
Simmer function	•
GasStop	•
Griddle surface width in mm	10 1/4 (258) in (mm)
Griddle surface depth in mm	17 1/8 (434) in (mm)

USER CONVENIENCE

Metal knobs •

Metal knobs	•
Backlit control knobs	•
Ergonomic swivel handle	•
Motorized lift-up control panel	•
Sabbath Program	•
Language Options	•
MyMiele	•
Clock synchronization	•
Time-of-day display	•
Date display	•
Timer	•
Safety shut-off	•
Programmable cooking duration	•
Actual temperature display	•
Recommended temperatures	•
Audible signal when desired temperature is reached	•
Favourites	•
Individual settings	•
Timed steam bursts	•
APPLIANCE DOOR	
CleanGlass door	•
Door contact switch	•
SoftClose oven door	•

OVEN COMPARTMENT

Oven capacity in I

5.76 (163) ft³ (I)

Number of oven shelf levels	6
Number of halogen lights	double
TwinPower Convection Fans	•

CLEANING CONVENIENCE

Stainless steel front with partial CleanTouch Steel finish	•
Self Clean oven	•
Heated catalyzer	•
Dishwasher-safe enamelled grates	•
Cooktop surface	Black enamel
	Heated

EFFICIENCY AND SUSTAINABILITY

Power-saving lighting circuit	•
Residual heat utilization	•
Rapid PreHeat	•

SAFETY

Appliance cooling system with touch-cool fronts	•
Safety shut-off	•
System lock	•
Door contact switch	•
Door lock during SelfClean	•

TECHNICAL DATA

Fresh-water connection for Moisture Plus	1.5
Appliance width in mm	36 1/8 (915)
Appliance height in mm (min.)	37 1/8 (942)
Appliance height in mm (max.)	38 5/8 (980)
Dimensions in mm (depth) with bullnose	27 1/2 (698)
Voltage in V	120
Voltage convertible in V	240/208
Fuse rating in A	40
Number of phases	1
Fresh-water connection for Moisture Plus	•

ACCESSORIES SUPPLIED

Anti-splash insert	1
Self Clean ready wire rack	2
Self Clean ready wire rack with rail system	1
Self Clean ready side racks	1
	1