Thiele/Small Parameters

41L782 T/S Parameters PDF (/app/products/caraudio/subs/l7/p41l782/files/41L782.pdf)

Rated Impedance [Ω]

2

Fs [Hz]

47.2

Sensitivity [1W, 1m]

82.4

Qts

0.735

Qms

8.828

Qes

0.802

Re [Ω]

6.6

Vas [ft³, L]

.322, 9.127

Recommended Amplifier Power (watts RMS)

500

Outer Frame Dimension [in, cm]

8-13/16, 22.4

Mounting Depth [in, cm]

5-7/16, 13.8

Mounting Cutout [in, cm]

7-1/4, 18.4

Frequency Response [Hz]

28 - 100

Sealed Enclosure Specs

Minimum Sealed Volume ft3 (L)

.4 (11.33)


Maximum Sealed Volume ft3 (L)

.75 (21.24)

Panel Dimensions for Minimum Sealed Enclosures using 3/4” (1.9cm) thick MDF

Box Volume [ft³, L]

.4 (11.33)



Panel A [in, cm]

11x11, 27.9x27.9

Panel B [in, cm]

11x7.75, 27.9x19.69

Panel C [in, cm]

9.5x7.75, 24.13x19.69

Vented Compact

Box Volume, ft³ (L) + port displacement

.66 (18.69)

Port Opening Size, in x in (cm x cm)

1.5x9.5 (3.8x24)

Port Length, in (cm)

19.25 (49)

Vented SQ

Box Volume, ft³ (L) + port displacement

1 (28.32)

Port Opening Size, in x in (cm x cm)

2x9.5 (5.1x24)

Port Length, in (cm)

21.25 (54)

*Assumes typical music program with minimal amplifier clipping; varies with enclosure size. See your KICKER dealer for details.

**Port Volume Excluded.

Due to continual developement, product, and specifications are subject to change without notice. Stillwater Designs and it's agents are not responsible for typographical errors.

You may also like these related products*