

**Product Specifications**

Style Number

Construction

Edge Profile

Nominal Dimensions

Actual Product Width

Actual Product Length

Wear Layer Thickness

Overall Product Thickness

Core Thickness

Attached Underlayment

Attached Underlayment

Thickness

Finish

Installation Methods

Profile

Country of Origin

**Packaging**

Area per Box

Pieces per Box

Weight per Box

Boxes per Pallet



905 Twilight Oak

40 boxes

**Colors**




905 Twilight Oak

Color Variation: Substantial




908 Fairweather Oak

Color Variation: Slight




912 Hayes Oak

Color Variation: Slight



913 Appalachian Pin

Color Variation: Substantial




914 Williamson Oak

Color Variation: Moderate




915 Waddington Oak

Color Variation: Slight




916 Venado Oak

Color Variation: Moderate



921 Tolima Pine

Color Variation: Moderate



922 Arvon Oak

Color Variation: Moderate

# COREtec Plus Enhanced XL

## Performance

|                                     |                 |
|-------------------------------------|-----------------|
| Static Load (ASTM F970)             | Passes          |
| Residual Indentation (ASTM F1914)   | Passes          |
| Resistance to Heat (ASTM F1514)     | Passes          |
| Resistance to Light (ASTM F1515)    | Passes          |
| Resistance to Chemicals (ASTM F925) | Passes          |
| Smoke Density (ASTM E662)           | Passes          |
| Radiant Panel (ASTM E648)           | Passes, Class I |
| Slip Resistance (ASTM D2047)        | ADA compliant   |

## Warranties

USF Lifetime

[Residential Resilient Limited Warranty - Defects, Wear, Waterproof, Petproof](#)

USF 10 Year Medium Commercial

## Certifications


GreenGuard (Certification, Gold, Private Label) Certified

## Coordinating Trim



**Baby Threshold\***

01V09 | 94"



**T-Molding\***

02V37 | 94"

02V40 | 94"

02V44 | 94"


02V45 | 94"

02V46 | 94"

02V47 | 94"


02V48 | 94"

02V50 | 94"




**Quarter Round**

01V35 | 94"



**Overlap Stairnose\***


01V83 | 94"



**Flush Stairnose**

FS7HU | 94"

02V10 | 94"



**Overlap Reducer**

01V59 | 94"

\*Packaged with molding track

## Stair Tread



**Stair Tread**

03Z70 | 48"

