# FRIGIDAIRE

PROFESSIONAL

# FPMO3077TF





**AVAILABLE COLORS** 



### SIGNATURE FEATURES



#### PowerPlus<sup>™</sup> 2-in-1 Convection Oven or Microwave

Get the great-tasting results of a conventional convection oven combined with the speed of microwave technology with the PowerPlus™ 2-in-1 Convection Microwave Oven.



**Smudge-Proof™ Stainless Steel** Resists fingerprints and cleans easily.



PowerSense™ Cooking Technology Results you can trust. PowerSense™ Cooking Technology automatically senses ideal time and power levels.

CONV COOK	COMBI COOK	SENSOR COOK	SENSOR REHEAT	MELI SOFTI
PREHEAT/ WARM	broil / Grill	DEFROST	VEGGIES	POPCC

#### PowerSense<sup>™</sup> Auto Defrost

Take the guesswork out of defrosting meat, poultry, or fish with PowerSense™ Auto Defrost.

# MICROWAVE

**30" BUILT-IN WITH CONVECTION** 

### **PRODUCT DIMENSIONS**

Height	19″
Width	29-13/16"
Depth	23"

#### MORE EASY-TO-USE FEATURES

PowerSense™ Broil & Grill Grill fresh or frozen pizza at the touch of a button.

#### PowerBright® LED Lighting

See the power. See the results in action. LED interior microwave light stays on while your dish cooks.

#### Keep Warm

Consistently keep your dishes warm, for up to 90 minutes, until everything and everyone is ready.

#### Drop-Down Door

Faster, easier access to what you are cooking with Drop-Down Door configuration.

#### Adjustable Timer

Now you can adjust the cooking time of your dish while it's cooking. The adjustable timer allows you to add 30 seconds on the timer.

## FPMO3077TF MICROWAVE 30" BUILT-IN WITH CONVECTION

#### FEATURES

PERIORES	
Control/Timing System	Pro-Select*
Exterior Door Finish	Smudge-Proof™ Stainless Steel
Handle Design	Stainless Steel
Microwave Capacity (Cu. Ft.)	1.6
PowerPlus™ Convection	Yes
Watts (IEC-705 Test Procedure)	1,000
Interior LED Light	Yes
Interior Color	Stainless Steel
Turntable Diameter	14-3/16"
Control Lock	Yes
Clock	Yes
Touch Pad Buttons	28
Power Levels	High (1-9)
Accessory Metal Rack	Yes

#### MICROWAVE CONTROL OPTIONS

Popcorn Button	Yes
Sensor Cook Button	Yes
Sensor Reheat Button	Yes
Broil/Grill	Yes
Preheat/Warm	Yes
Melt & Soften Options	4
Auto Defrost Options	3
Multi-Stage Cooking Option	Yes
Keep Warm	Yes
Add 30 Seconds	Yes
Sensor Cooking Options	5
Sensor Reheat Options	5
Vegetable Cook Sensor	Yes
User Preferences	Yes
Adjustable Timer	Yes
POWER RATINGS	
Frequency (MHz)	2,450
Watts @ 120 Volts	1,750
Amps @ 120 Volts	15.5
SPECIFICATIONS	
Oven Interior (HxWxD)	9-27/32"×16-1/2"×16-1/2"
Power Supply Connection Location	Right Top Rear
Voltage Rating	120V/60Hz/20A
Connected Load (kW Rating) @ 120 Volts <sup>1</sup>	1.75
Minimum Circuit Required (Amps)	20
Plug Type (NEMA)	LCDI (5-20P)
Shipping Weight (Approx.)	100 Lbs.
Ear use on adequately wired 1201/ dedicated circ	uit baving 2-wire service with

For use on adequately wired 120V, dedicated circuit having 2-wire service with a separate ground wire. Appliance must be grounded for safe operation.

#### PRODUCT DIMENSIONS

A-Height	19″	
B-Width	29-13/16"	
C-Depth	23"	
CUTOUT DIMENSIONS		
Height (Min Max.)	17-3/4" - 18"	
Width (Min Max.)	28" - 28-3/8"	
Depth (Min.)	22"	





Note: For planning purposes only. Always consult local and national electric, gas and plumbing codes. Refer to Product Installation Guide for detailed installation instructions on the web at frigidaire.com / frigidaire.ca Specifications subject to change. Accessories information available on the web at frigidaire.com / frigidaire.ca

FRIGIDAIRE -



## INSTALLATION SPECIFICATIONS

- Product Shipping Weight (Approx.) 100 Lbs.
- Voltage Rating 120V/60 Hz/20 Amps
- Connected Load (kW Rating) @ 120 Volts = 1.75 kW
- (For use on adequately wired 120V, dedicated circuit having 2-wire service with a separate ground wire. Appliance must be grounded for safe operation.)
- Amps @ 120 Volts = 20 Amps
- Always consult local and national electric codes.
- Microwave can stand alone on countertop or be built in with optional 30" or 27" Trim Kit (ordered by individual part number) which includes Bottom
- Duct Assembly shipped in separate box. Allow 21" minimum clearance for 90° door swing.
- Minimum 22" deep oven cutout dimension is critical for proper installation for oven and faceplate to fit flush against cabinet front.

- · Consult local building code, in the event that cutout opening may be required to be enclosed with sides, ceiling and rear partition.
- Full oven base of solid plywood or similar material required, capable of supporting 155 Lbs.
- · Base must be level and front of cabinet square for proper operation.
- Can NOT be installed above any gas wall oven.
- Built-In Microwave is approved to be used in combination with any Frigidaire® Electric Single Wall Oven and /or Warmer Drawer. (*Refer to model-specific* Combination Installation Specification pages on web.)
- When used in combination with another Frigidaire® built-in product, a minimum clearance of 2" is required from the bottom of the microwave cutout to the top edge of the companion product's faceplate. Please refer to companion product's installation instructions for cutout dimensions.



FRIGIDAIRE

Note: For planning purposes only. Always consult local and national electric, gas and plumbing codes. Refer to Product Installation Guide for detailed installation instructions on the web at frigidaire.com / frigidaire.ca. Specifications subject to change. Accessories information available on the web at frigidaire.com / frigidaire.ca

USA • 10200 David Taylor Drive • Charlotte, NC 28262 • 1-800-FRIGIDAIRE • frigidaire.com CANADA • 5855 Terry Fox Way • Mississauga, ON L5V 3E4 • 1-800-265-8352 • frigidaire.ca