

# General Specifications

## ■Type

PRIMARY SPEAKER: Built-in amplifier, 2-way bass reflex type, detachable speaker grill

SECONDARY SPEAKER: 2-way bass reflex type, detachable speaker grill

## ■Speakers used

Woofer : 4inch(101.60mm) , Tweeter : 3/4inch (19mm)

## ■Amplifier configurations

Bi-Amplifier

## ■Power Output

2 ch × 25 W(HF:8W + LF:17W) at 8 ohms, HF:10 kHz, 2 ch driven of 1% THD, LF:100 Hz, 2 ch driven of 1% THD

## ■Input terminals

Analogue

- AUX terminal (φ3.5mm stereo mini plug) ×1
- RCA stereo terminal (LINE/PHONO) ×1

Digital

- Optical digital terminal (PCM 2ch/32kHz, 44.1kHz, 48kHz) ×1
- USB Type-C terminal ×1
- HDMI (ARC) terminal ×1

## ■Output terminal

HDMI ARC terminal

SUBWOOFER terminal

## ■Other terminals

Speaker terminal

GND terminal

## ■BLUETOOTH Section

Communication system

- Bluetooth Specification version 5.3 + dual mode

Frequency band

- 2.4GHz (2.402-2.480GHz)

Modulation method

- FHSS (Frequency Hopping Spread Spectrum)

Compatible BLUETOOTH profiles

- A2DP 1.3.2, AVRCP 1.6.2, HFP1.8, HSP 1.2, SPP 1.2

Supported Codecs

- SBC

Transmission range (A2DP)

- 20 Hz - 20 kHz (Sampling frequency 44.1kHz)




Maximum communication range

- Line of sight approx. 15 m(\*)

(\*)The actual range will vary depending on factors such as obstacles between devices, magnetic fields around a microwave oven, static electricity, cordless phone, reception sensitivity, antenna's performance, operating system, software application, etc.

Maximum radio-frequency power transmitted in the frequency band(s)

- 2400 MHz - 2483.5 MHz (20 dBm (e.i.r.p))



## ■USB Section

USB Ver.2.0, Type-C

## ■HDMI Section

ARC compatible audio format: PCM

## ■General

Power Supply

- AC 100 - 240 V, 50/60 Hz

Power Consumption

- 10 W

Standby mode

- BLUETOOTH : 0.3 W
- HDMI : 0.3 W
- USB : 0.3 W
- AUX : 0.3 W
- OPTICAL : 0.3 W
- RCA : 0.3 W

\*In this mode, when there is no signal output, the idle power consumption is 0.3 W after 15 minutes.

Dimensions (W × H × D)

- PRIMARY SPEAKER : 146 mm × 224 mm × 188 mm (including speaker grilles and protrusions on the back)
- SECONDARY SPEAKER : 146 mm × 224 mm × 180 mm (including speaker grilles and protrusions on the back)

Weight

- PRIMARY SPEAKER : 2.8 kg (including speaker grill)
- SECONDARY SPEAKER : 2.6 kg (including speaker grill)

## ■License and Trademark



The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing Administrator, Inc. in the United States and other countries.



The BLUETOOTH® word mark and logos are registered trademarks owned by BLUETOOTH SIG, Inc.

All other trademarks are the property of their respective owners.

