

Specifications

Description: Integrated Powered Loudspeaker system with Phono Preamp and Bluetooth compatible wireless Transmitter and Receiver.

	SpinBase 2	SpinBase MAX 2
Inputs	Magnetic Phono, Aux (Line), Optical, BT compatible Wireless, USB Flash Drive	
Phono Input impedance	47kOhm, 100pF	
Line Input impedance	10kOhm	
Optical input resolution	24Bit/96kHz	
USB File Format	MP3, WMA, WAV	
Headphone Output	120mW @ 16 Ohms	
Line Output	2V RMS	
USB Power	5VDC /300mA	
Power input	100-240V AC / 50-60 Hz/ 1.5A	
Amplifier Type	Dual Direct Drive class-D	
Tweeters	Two 3/4" silk dome	
Woofers	Two 1-3/4" x 4" Oval	Four 3-1/2" round
Woofer amplifier power	20 W/Channel	35 W/Channel
Tweeter Amplifier Power	15 W/Channel	15 W/Channel
Enclosure type	Reflex Vented braced MDF	Sealed Acoustic-Suspension MDF
Frequency Range	65Hz - 20kHz	50Hz - 20kHz
Dimensions W x H x D (inch)	18" x 13.5" x 3.25"	18" x 13.5" x 4.25"
Dimensions W x H x D (mm)	458mm x 343mm x 83mm	458mm x 343mm x 102mm

Andover Audio subscribes to a program of continuous improvement. As a result, some product features and characteristics may change without prior notice.