





# 600 CFM/14,0 SONES @ 0.10" SP.

#### **Dimensions**

Overall bottom projection - 193/4" Height (less chimney) - 111/8" Available widths: 30", 36", 48"

### **Hood Body**

Brushed stainless steel.

### Motor

3 speed, permanently split capacitor motor. Rated 120 volts, 60 hz.

### Lighting

Two - GU10 base, MR16, 50 watt halogen lights.

# **Ducting Options**

Vertical ducting: 6" round duct adapter complete with polymetric back draft damper ensuring quiet operation. Ductless: Requiers charcoal filter (not included).

## **Blower Wheel**

Dual inlet, electronically balanced polymetric centrifugal blower wheel,  $5^{3/4}$ " width 59 paddles.

### Mounting

Ceiling mounted with included mounting bracket. Install 20" to 30" from cooking surface.

# **Filters**


Grease Filter: BCGF-01 (included). Charcoal Filter: BCCF-01 (not included).

### **Available Finishes**

Stainless Steel.







EXPANDED PERFORMANCE											
		Stati	c Pressure	(inches d	Sones	Fan Speed	Power				
	0	0.1	0.25	0.5	0.75	1.0	@ .1 SP	RPM	Watts	Amps	
Air Flow - CFM	609	600	587	568	546	520	14.0	2560	542.0	2.8	

PROJECT							ARCHITECT			
LOCATION							ENGINEER			
CONTRACTOR							SUBMITTI	SUBMITTED BY DATE		
FAN NUMBER	MODEL NUMBER	CFM	IN W.C.	RPM	WATTS	AMPS	SONES	QTY	OPTIONAL EQUIPMENT & REMARKS	



U.S.: 820 Lincoln Avenue West Chester, Pennsylvania 19380-4466 Tel: (610) 692-7400 • 877-304-3785

Fax: (610) 696-8048

Canada: 8 Edvac Drive Brampton, Ontario L6S 5P2 Tel: (905) 456-2033 • 800-250-8767 Fax: (905) 456-1015

Updated 2-13 Specifications subject to change without notice.