

PFD 104 SCVi XXL

Fully integrated Full-sizedishwasher with 3D MultiFlex cutlery tray for large loads of dishware in households, offices and utility areas.

I



- Wash performance: 16 place settings in just 52 min.*
- Flexible loading of wash items for the best cleaning results
- Door opens automatically after two knocks – Knock2open
- Everything completely dry AutoOpen assisted drying
- Innovative design and maximum convenience 3D MultiFlex Tray

Depending on site conditions (temperature of incoming water / power connection) values given may vary.

EAN: 4002516366881 / Material number: 11605450 / Old Material Number: 61010405USA

| Model and design | - |
|--|-----------------------------|
| Number of levels | 2 |
| Front | Without front |
| Side walls | Galvanised |
| Fascia color | Obsidianschwarz |
| Application | |
| Suitable for retirement and care homes | • |
| Suitable for hospitals | • |
| Suitable for Bed & Breakfast | • |
| Suitable for child care facilities | • |
| Suitable for universities and schools | • |
| Suitable for offices | • |
| Suitable for domestic use | • |
| Suitable for small businesses | • |
| Suitable for sports clubs | • |
| Performance data | |
| Tested virucidal efficacy | • |
| Circulation pump, Qmax in gal/min (l/min) | 283.9 (75) |
| Service life in wash cycles | 12500 |
| Controls | |
| Program selection | Program Selector Buttons |
| Program sequence indicator | • |
| Standard electrical connection | |
| Electrical connection | AC 120V 60HZ |
| Heater rating in kW | 1.30 |
| Total connected load in kW | 1.40 |
| Fuse rating in A | 15 |
| Length of power cord in ft (m) | 5 (1.70) |
| NEMA plug: 5-15 | • |
| Possible voltage variant 1 | |
| Electrical connection | 2N AC 120/208-240V, 60HZ |
| Heater rating in kW | 3.50-3.80 |
| Total connected load in kW | 3.70-4.00 |
| Fuse rating in A | 30 |
| Water connection/drainage | |
| Required flow pressure in bar | 0.30-10.00 |
| Drain hose [DN] | 22 |
| Maximum delivery head for drain pump in inches (cm) | 39 3/8 (100) |
| Water protection system | Waterproof system |
| Dimensions and weight | |
| External dimensions, gross height in inches | 37 7/8 (960) |
| External dimensions, gross width in inches | 26 1/2 (670) |
| External dimensions, gross depth in inches | 27 5/8 (700) |
| Usable space in wash cabinet, width in inches (mm) | 22 7/8 (580) |
| Usable space in wash cabinet, height in inches (mm) | 20 1/8 (510) |
| Usable space in wash cabinet, depth of upper basket in inches (mm) | 17 3/4 (450) |
| Usable space in wash cabinet, depth of lower basket in inches (mm) | 17 3/4 (450) |
| In-feed height above floor in inches (mm) | 8 3/8 (210) |
| | |



PFD 104 SCVi XXL

Fully integrated Full-sizedishwasher with 3D MultiFlex cutlery tray for large loads of dishware in households, offices and utility areas.





| Gross weight in lbs. | 128 (58) |
|---|----------|
| Maximum floor loading in N | 1000 |
| Emissions data | |
| Sound power (LwA) in dB(A) re 1 pW | 45.0 |
| Programs | |
| Universal | • |
| Short | • |
| SaniWash | • |
| Cold/Pre-wash | • |
| Glasses | • |
| Plastic | • |
| Intensive | • |
| Basket design | |
| Flexible FlexLine basket design | • |
| FlexCare glass holder [number] | 4 |
| FlexCare cup rack [number] | 2 |
| Height-adjustable upper basket | • |
| Patented 3D MultiFlex tray | • |
| Features | |
| Commercial-grade electrical connection | • |
| Wash cabinet made from high-quality stainless steel | • |
| Knock2open | • |
| AutoOpen assisted drying | • |
| AutoClose | • |
| EcoFeedback | • |
| Brilliant GlassCare | • |
| Adjustable final rinse temperature | • |
| Optical interface | • |
| SmartStart | • |
| Test certificate | |
| UL | • |

EAN: 4002516366881 / Material number: 11605450 / Old Material Number: 61010405USA