



# **RA-12** Integrated Amplifier



# Connectivity without compromise

Music has changed. Today we can stream it, download it, play whatever we like, whenever we like. But all too often, this convenience has come with a price: sound quality. That is, until now. Our new RA-12 has all the connectivity you need to make the most of your digital music. And the advanced audiophile technology to really bring it to life. The RA-12 - uncompromising sound, for a connected world.





















**RA-12** Specifications





#### **Continuous Power Output**

60Watts/ch (20-20kHz, < 0.03%, 8Ω)

#### Total Harmonic Distortion (20Hz-20kHz)

< 0.03% at rated power

# **Intermodulation Distortion** (60 Hz:7 kHz, 4:1)

< 0.03% at rated power

# Frequency Response

Phono input 20Hz-15kHz, ±0.3dB Line Level Inputs 10Hz-100kHz, ±1dB

# Input Sensitivity / Impedance

Phono input 2.5mV / 47 k  $\Omega$ Line Level Inputs 150mV / 24 k  $\Omega$ 

# Input Overload

Phono input 180mV Line Level Inputs 5V

# Preamp Output / Impedance

 $1V / 470\Omega$ 

#### Tone Controls - Bass / Treble

±4 dB at 100Hz / 10kHz

# Signal to Noise Ratio

# (IHF "A" weighted)

Phono input 80dB Line Level Inputs 100dB

# **DIGITAL SECTION**

# **Frequency Response**

10Hz-95kHz ±3.0dB (MAX)

# Signal to Noise Ratio

(IHF "A" weighted) 100dB

# Input Sensitivity/Impedance

0 dBfs/75V

#### Pre-out/Impedance

1.2V/470V (at -20dB)

# Decodable Front USB/iPod Digital **Signals**

AAC (m4a), WAV, MP3, WMA (up to 48K 16bit)

# Coaxial/Optical Inputs

LPCM up to 192kHz 24bit

#### **File Formats**

(depend on the source PC in use) Real Audio, MP3, OGG Vorbis, WAV, AIFF, AU

# **GENERAL**

# Power Requirements (AC)

120V, 60Hz (USA) 230V, 50Hz (Europe)

# **Power Consumption**

300Watts

# **Standby Power** Consumption 0.5W

0.5Watts

# Dimensions (W x H x D)

430 x 92 x 342mm 17 x 3 5/8 x 13 1/2 in

# Panel Height

80mm (3 1/16 ins)

# Weight (Net)

8.02kg (18lbs)

# **Finishes**

Black

Silver

www.rotel.com 1.10.13