Product data sheet

CONSTRUCTION TYPE

Fully integrated dishwashers	•
60 cm dishwashers	•

DESIGN

Control panel colour	Stainless Steel.
Control panel version	Fully integrated fascia
Control type	Programme selector button
Display	3-digit 7-segment display
Display colour	Yellow

CONVENIENCE

Door closing aid	ComfortClose
Time left display	•
Delay start up to 24 h	•
In-operation indicator light	acoustic
Operating noise dB(A) re 1 pW	44

EFFICIENCY AND SUSTAINABILITY

Hot-water connection	•	
Proven hygiene	•	
ENERGY STAR® Most Efficient	•	

0/19/23, 4:32 PM	G 5051 SCVi Active Miele
EcoPower technology	•
QUALITY OF RESULTS	
Fresh-water dishwasher	•
WASH PROGRAMS	
Automatic	•
Intensive 75°C	•
QuickIntenseWash	•
Sanitize	•
Rinse & Hold	•
CLEANING OPTIONS	
Short	•
Extra clean	•
Extra dry	•
TECHNICAL DATA	
Minimum niche height in mm	32 1/8 (815)
Appliance width in mm	23 5/8 (598)
Appliance height in mm	32 1/8 (815)
Appliance depth in mm	22 1/2 (570)
Appliance depth with door open in cm	45 7/8 (116.5)
Net weight in kg	98 (44.0)

1.400

120

Total rated load in kW

Voltage in V

Fuse rating in A	15
Number of phases	1
Electrical frequency standard	60
Length of water inlet hose in cm	5 (1.50)
Length of water drain hose in cm	5 (1.50)
Length of power cable in m	4 (1.20)
Minimum niche width in mm	23 5/8 (600)
Niche depth in mm	21 3/4 (550)
Maximum niche width in mm	23 5/8 (600)
Maximum niche height in mm	34 3/4 (880)
Min. front panel weight in kg	4.0
Max. front panel weight in kg	11.0
[retro-fittable by Service to min.]	8.0
[retro-fittable by Service to max.]	16.0

BASKET DESIGN

Cutlery loading	Cutlery tray
Basket design	Comfort
FlexCare cup rack	1

SAFETY

Waterproof system