

		Front Camera	Rear Camera
Hard Specification	Screen size	-	-
	Operating voltage	5V / 2A; 12-24V DC	DC 5V
	Current Consumption	320mA	110mA
	Super Capacitor	Yes	-
	Button	Tact	-
	Wireless Link	Yes	-
	Microphone	Built-in	-
	Speaker	Built-in	-
	GPS Receiver	Built-in	-
	G-sensor	Built-in	-
	Collision sensitivity	-4.0G to +4.0G (0.1G Step)	-
	Image sensor	1/2.8 CMOS sensor	1/2.8 CMOS sensor
	Valid Pixel	5.14M Pixels(2616 x 1964)	2.12M Pixels(1936x1097)
	Number of Pixel	3.7M Pixels (2560 x 1440)	2M Pixels(1920x1080)
	Angles of view	Horizontal : 114° Vertical : 82° Diagonal :154°	Horizontal : 129° Vertical : 66° Diagonal :161°
	Lens rotation	Yes	Yes(180°)
	Image reversal (Upside down)	Yes	-
	Lens	F1.8	F2.0
	Polarization Filter	Bundled	No
	Operating temperature	-10°C to +60°C	-10°C to +60°C
	Noise Protection	Yes	Yes
OSD Menu Language	Implemented languages	EN/DE/FR/NL/IT/ES/PT/RU/PL/CZ/RO	-

		Front Camera	Rear Camera
Hard Specification	Screen size	-	-
	Operating voltage	5V / 2A; 12-24V DC	DC 5V
	Current Consumption	320mA	110mA
	Super Capacitor	Yes	-
	Button	Tact	-
	Wireless Link	Yes	-
	Microphone	Built-in	-
	Speaker	Built-in	-
	GPS Receiver	Built-in	-
	G-sensor	Built-in	-
	Collision sensitivity	-4.0G to +4.0G (0.1G Step)	-
	Image sensor	1/2.8 CMOS sensor	1/2.8 CMOS sensor
	Valid Pixel	5.14M Pixels(2616 x 1964)	2.12M Pixels(1936x1097)
	Number of Pixel	3.7M Pixels (2560 x 1440)	2M Pixels(1920x1080)
	Angles of view	Horizontal : 114° Vertical : 82° Diagonal :154°	Horizontal : 129° Vertical : 66° Diagonal :161°
	Lens rotation	Yes	Yes(180°)
	Image reversal (Upside down)	Yes	-
	Lens	F1.8	F2.0
	Polarization Filter	Bundled	No
	Operating temperature	-10°C to +60°C	-10°C to +60°C
	Noise Protection	Yes	Yes
OSD Menu Language	Implemented languages	EN/DE/FR/NL/IT/ES/PT/RU/PL/CZ/RO	-

		Front Camera	Rear Camera
Hard Specification	Screen size	-	-
	Operating voltage	5V / 2A; 12-24V DC	DC 5V
	Current Consumption	320mA	110mA
	Super Capacitor	Yes	-
	Button	Tact	-
	Wireless Link	Yes	-
	Microphone	Built-in	-
	Speaker	Built-in	-
	GPS Receiver	Built-in	-
	G-sensor	Built-in	-
	Collision sensitivity	-4.0G to +4.0G (0.1G Step)	-
	Image sensor	1/2.8 CMOS sensor	1/2.8 CMOS sensor
	Valid Pixel	5.14M Pixels(2616 x 1964)	2.12M Pixels(1936x1097)
	Number of Pixel	3.7M Pixels (2560 x 1440)	2M Pixels(1920x1080)
	Angles of view	Horizontal : 114° Vertical : 82° Diagonal :154°	Horizontal : 129° Vertical : 66° Diagonal :161°
	Lens rotation	Yes	Yes(180°)
	Image reversal (Upside down)	Yes	-
	Lens	F1.8	F2.0
	Polarization Filter	Bundled	No
	Operating temperature	-10°C to +60°C	-10°C to +60°C
	Noise Protection	Yes	Yes
OSD Menu Language	Implemented languages	EN/DE/FR/NL/IT/ES/PT/RU/PL/CZ/RO	-

		Front Camera	Rear Camera
Hard Specification	Screen size	-	-
	Operating voltage	5V / 2A; 12-24V DC	DC 5V
	Current Consumption	320mA	110mA
	Super Capacitor	Yes	-
	Button	Tact	-
	Wireless Link	Yes	-
	Microphone	Built-in	-
	Speaker	Built-in	-
	GPS Receiver	Built-in	-
	G-sensor	Built-in	-
	Collision sensitivity	-4.0G to +4.0G (0.1G Step)	-
	Image sensor	1/2.8 CMOS sensor	1/2.8 CMOS sensor
	Valid Pixel	5.14M Pixels(2616 x 1964)	2.12M Pixels(1936x1097)
	Number of Pixel	3.7M Pixels (2560 x 1440)	2M Pixels(1920x1080)
	Angles of view	Horizontal : 114° Vertical : 82° Diagonal :154°	Horizontal : 129° Vertical : 66° Diagonal :161°
	Lens rotation	Yes	Yes(180°)
	Image reversal (Upside down)	Yes	-
	Lens	F1.8	F2.0
	Polarization Filter	Bundled	No
	Operating temperature	-10°C to +60°C	-10°C to +60°C
	Noise Protection	Yes	Yes
OSD Menu Language	Implemented languages	EN/DE/FR/NL/IT/ES/PT/RU/PL/CZ/RO	-

		Front Camera	Rear Camera
Hard Specification	Screen size	-	-
	Operating voltage	5V / 2A; 12-24V DC	DC 5V
	Current Consumption	320mA	110mA
	Super Capacitor	Yes	-
	Button	Tact	-
	Wireless Link	Yes	-
	Microphone	Built-in	-
	Speaker	Built-in	-
	GPS Receiver	Built-in	-
	G-sensor	Built-in	-
	Collision sensitivity	-4.0G to +4.0G (0.1G Step)	-
	Image sensor	1/2.8 CMOS sensor	1/2.8 CMOS sensor
	Valid Pixel	5.14M Pixels(2616 x 1964)	2.12M Pixels(1936x1097)
	Number of Pixel	3.7M Pixels (2560 x 1440)	2M Pixels(1920x1080)
	Angles of view	Horizontal : 114° Vertical : 82° Diagonal :154°	Horizontal : 129° Vertical : 66° Diagonal :161°
	Lens rotation	Yes	Yes(180°)
	Image reversal (Upside down)	Yes	-
	Lens	F1.8	F2.0
	Polarization Filter	Bundled	No
	Operating temperature	-10°C to +60°C	-10°C to +60°C
	Noise Protection	Yes	Yes
OSD Menu Language	Implemented languages	EN/DE/FR/NL/IT/ES/PT/RU/PL/CZ/RO	-

		Front Camera	Rear Camera
Hard Specification	Screen size	-	-
	Operating voltage	5V / 2A; 12-24V DC	DC 5V
	Current Consumption	320mA	110mA
	Super Capacitor	Yes	-
	Button	Tact	-
	Wireless Link	Yes	-
	Microphone	Built-in	-
	Speaker	Built-in	-
	GPS Receiver	Built-in	-
	G-sensor	Built-in	-
	Collision sensitivity	-4.0G to +4.0G (0.1G Step)	-
	Image sensor	1/2.8 CMOS sensor	1/2.8 CMOS sensor
	Valid Pixel	5.14M Pixels(2616 x 1964)	2.12M Pixels(1936x1097)
	Number of Pixel	3.7M Pixels (2560 x 1440)	2M Pixels(1920x1080)
	Angles of view	Horizontal : 114° Vertical : 82° Diagonal :154°	Horizontal : 129° Vertical : 66° Diagonal :161°
	Lens rotation	Yes	Yes(180°)
	Image reversal (Upside down)	Yes	-
	Lens	F1.8	F2.0
	Polarization Filter	Bundled	No
	Operating temperature	-10°C to +60°C	-10°C to +60°C
	Noise Protection	Yes	Yes
OSD Menu Language	Implemented languages	EN/DE/FR/NL/IT/ES/PT/RU/PL/CZ/RO	-

		Front Camera	Rear Camera
Hard Specification	Screen size	-	-
	Operating voltage	5V / 2A; 12-24V DC	DC 5V
	Current Consumption	320mA	110mA
	Super Capacitor	Yes	-
	Button	Tact	-
	Wireless Link	Yes	-
	Microphone	Built-in	-
	Speaker	Built-in	-
	GPS Receiver	Built-in	-
	G-sensor	Built-in	-
	Collision sensitivity	-4.0G to +4.0G (0.1G Step)	-
	Image sensor	1/2.8 CMOS sensor	1/2.8 CMOS sensor
	Valid Pixel	5.14M Pixels(2616 x 1964)	2.12M Pixels(1936x1097)
	Number of Pixel	3.7M Pixels (2560 x 1440)	2M Pixels(1920x1080)
	Angles of view	Horizontal : 114° Vertical : 82° Diagonal :154°	Horizontal : 129° Vertical : 66° Diagonal :161°
	Lens rotation	Yes	Yes(180°)
	Image reversal (Upside down)	Yes	-
	Lens	F1.8	F2.0
	Polarization Filter	Bundled	No
	Operating temperature	-10°C to +60°C	-10°C to +60°C
	Noise Protection	Yes	Yes
OSD Menu Language	Implemented languages	EN/DE/FR/NL/IT/ES/PT/RU/PL/CZ/RO	-

		Front Camera	Rear Camera
Hard Specification	Screen size	-	-
	Operating voltage	5V / 2A; 12-24V DC	DC 5V
	Current Consumption	320mA	110mA
	Super Capacitor	Yes	-
	Button	Tact	-
	Wireless Link	Yes	-
	Microphone	Built-in	-
	Speaker	Built-in	-
	GPS Receiver	Built-in	-
	G-sensor	Built-in	-
	Collision sensitivity	-4.0G to +4.0G (0.1G Step)	-
	Image sensor	1/2.8 CMOS sensor	1/2.8 CMOS sensor
	Valid Pixel	5.14M Pixels(2616 x 1964)	2.12M Pixels(1936x1097)
	Number of Pixel	3.7M Pixels (2560 x 1440)	2M Pixels(1920x1080)
	Angles of view	Horizontal : 114° Vertical : 82° Diagonal :154°	Horizontal : 129° Vertical : 66° Diagonal :161°
	Lens rotation	Yes	Yes(180°)
	Image reversal (Upside down)	Yes	-
	Lens	F1.8	F2.0
	Polarization Filter	Bundled	No
	Operating temperature	-10°C to +60°C	-10°C to +60°C
	Noise Protection	Yes	Yes
OSD Menu Language	Implemented languages	EN/DE/FR/NL/IT/ES/PT/RU/PL/CZ/RO	-

		Front Camera	Rear Camera
Hard Specification	Screen size	-	-
	Operating voltage	5V / 2A; 12-24V DC	DC 5V
	Current Consumption	320mA	110mA
	Super Capacitor	Yes	-
	Button	Tact	-
	Wireless Link	Yes	-
	Microphone	Built-in	-
	Speaker	Built-in	-
	GPS Receiver	Built-in	-
	G-sensor	Built-in	-
	Collision sensitivity	-4.0G to +4.0G (0.1G Step)	-
	Image sensor	1/2.8 CMOS sensor	1/2.8 CMOS sensor
	Valid Pixel	5.14M Pixels(2616 x 1964)	2.12M Pixels(1936x1097)
	Number of Pixel	3.7M Pixels (2560 x 1440)	2M Pixels(1920x1080)
	Angles of view	Horizontal : 114° Vertical : 82° Diagonal :154°	Horizontal : 129° Vertical : 66° Diagonal :161°
	Lens rotation	Yes	Yes(180°)
	Image reversal (Upside down)	Yes	-
	Lens	F1.8	F2.0
	Polarization Filter	Bundled	No
	Operating temperature	-10°C to +60°C	-10°C to +60°C
	Noise Protection	Yes	Yes
OSD Menu Language	Implemented languages	EN/DE/FR/NL/IT/ES/PT/RU/PL/CZ/RO	-

		Front Camera	Rear Camera
Hard Specification	Screen size	-	-
	Operating voltage	5V / 2A; 12-24V DC	DC 5V
	Current Consumption	320mA	110mA
	Super Capacitor	Yes	-
	Button	Tact	-
	Wireless Link	Yes	-
	Microphone	Built-in	-
	Speaker	Built-in	-
	GPS Receiver	Built-in	-
	G-sensor	Built-in	-
	Collision sensitivity	-4.0G to +4.0G (0.1G Step)	-
	Image sensor	1/2.8 CMOS sensor	1/2.8 CMOS sensor
	Valid Pixel	5.14M Pixels(2616 x 1964)	2.12M Pixels(1936x1097)
	Number of Pixel	3.7M Pixels (2560 x 1440)	2M Pixels(1920x1080)
	Angles of view	Horizontal : 114° Vertical : 82° Diagonal :154°	Horizontal : 129° Vertical : 66° Diagonal :161°
	Lens rotation	Yes	Yes(180°)
	Image reversal (Upside down)	Yes	-
	Lens	F1.8	F2.0
	Polarization Filter	Bundled	No
	Operating temperature	-10°C to +60°C	-10°C to +60°C
	Noise Protection	Yes	Yes
OSD Menu Language	Implemented languages	EN/DE/FR/NL/IT/ES/PT/RU/PL/CZ/RO	-

		Front Camera	Rear Camera
Hard Specification	Screen size	-	-
	Operating voltage	5V / 2A; 12-24V DC	DC 5V
	Current Consumption	320mA	110mA
	Super Capacitor	Yes	-
	Button	Tact	-
	Wireless Link	Yes	-
	Microphone	Built-in	-
	Speaker	Built-in	-
	GPS Receiver	Built-in	-
	G-sensor	Built-in	-
	Collision sensitivity	-4.0G to +4.0G (0.1G Step)	-
	Image sensor	1/2.8 CMOS sensor	1/2.8 CMOS sensor
	Valid Pixel	5.14M Pixels(2616 x 1964)	2.12M Pixels(1936x1097)
	Number of Pixel	3.7M Pixels (2560 x 1440)	2M Pixels(1920x1080)
	Angles of view	Horizontal : 114° Vertical : 82° Diagonal :154°	Horizontal : 129° Vertical : 66° Diagonal :161°
	Lens rotation	Yes	Yes(180°)
	Image reversal (Upside down)	Yes	-
	Lens	F1.8	F2.0
	Polarization Filter	Bundled	No
	Operating temperature	-10°C to +60°C	-10°C to +60°C
	Noise Protection	Yes	Yes
OSD Menu Language	Implemented languages	EN/DE/FR/NL/IT/ES/PT/RU/PL/CZ/RO	-

		Front Camera	Rear Camera
Hard Specification	Screen size	-	-
	Operating voltage	5V / 2A; 12-24V DC	DC 5V
	Current Consumption	320mA	110mA
	Super Capacitor	Yes	-
	Button	Tact	-
	Wireless Link	Yes	-
	Microphone	Built-in	-
	Speaker	Built-in	-
	GPS Receiver	Built-in	-
	G-sensor	Built-in	-
	Collision sensitivity	-4.0G to +4.0G (0.1G Step)	-
	Image sensor	1/2.8 CMOS sensor	1/2.8 CMOS sensor
	Valid Pixel	5.14M Pixels(2616 x 1964)	2.12M Pixels(1936x1097)
	Number of Pixel	3.7M Pixels (2560 x 1440)	2M Pixels(1920x1080)
	Angles of view	Horizontal : 114° Vertical : 82° Diagonal :154°	Horizontal : 129° Vertical : 66° Diagonal :161°
	Lens rotation	Yes	Yes(180°)
	Image reversal (Upside down)	Yes	-
	Lens	F1.8	F2.0
	Polarization Filter	Bundled	No
	Operating temperature	-10°C to +60°C	-10°C to +60°C
	Noise Protection	Yes	Yes
OSD Menu Language	Implemented languages	EN/DE/FR/NL/IT/ES/PT/RU/PL/CZ/RO	-

		Front Camera	Rear Camera
Hard Specification	Screen size	-	-
	Operating voltage	5V / 2A; 12-24V DC	DC 5V
	Current Consumption	320mA	110mA
	Super Capacitor	Yes	-
	Button	Tact	-
	Wireless Link	Yes	-
	Microphone	Built-in	-
	Speaker	Built-in	-
	GPS Receiver	Built-in	-
	G-sensor	Built-in	-
	Collision sensitivity	-4.0G to +4.0G (0.1G Step)	-
	Image sensor	1/2.8 CMOS sensor	1/2.8 CMOS sensor
	Valid Pixel	5.14M Pixels(2616 x 1964)	2.12M Pixels(1936x1097)
	Number of Pixel	3.7M Pixels (2560 x 1440)	2M Pixels(1920x1080)
	Angles of view	Horizontal : 114° Vertical : 82° Diagonal :154°	Horizontal : 129° Vertical : 66° Diagonal :161°
	Lens rotation	Yes	Yes(180°)
	Image reversal (Upside down)	Yes	-
	Lens	F1.8	F2.0
	Polarization Filter	Bundled	No
	Operating temperature	-10°C to +60°C	-10°C to +60°C
	Noise Protection	Yes	Yes
OSD Menu Language	Implemented languages	EN/DE/FR/NL/IT/ES/PT/RU/PL/CZ/RO	-

		Front Camera	Rear Camera
Hard Specification	Screen size	-	-
	Operating voltage	5V / 2A; 12-24V DC	DC 5V
	Current Consumption	320mA	110mA
	Super Capacitor	Yes	-
	Button	Tact	-
	Wireless Link	Yes	-
	Microphone	Built-in	-
	Speaker	Built-in	-
	GPS Receiver	Built-in	-
	G-sensor	Built-in	-
	Collision sensitivity	-4.0G to +4.0G (0.1G Step)	-
	Image sensor	1/2.8 CMOS sensor	1/2.8 CMOS sensor
	Valid Pixel	5.14M Pixels(2616 x 1964)	2.12M Pixels(1936x1097)
	Number of Pixel	3.7M Pixels (2560 x 1440)	2M Pixels(1920x1080)
	Angles of view	Horizontal : 114° Vertical : 82° Diagonal :154°	Horizontal : 129° Vertical : 66° Diagonal :161°
	Lens rotation	Yes	Yes(180°)
	Image reversal (Upside down)	Yes	-
	Lens	F1.8	F2.0
	Polarization Filter	Bundled	No
	Operating temperature	-10°C to +60°C	-10°C to +60°C
	Noise Protection	Yes	Yes
OSD Menu Language	Implemented languages	EN/DE/FR/NL/IT/ES/PT/RU/PL/CZ/RO	-

		Front Camera	Rear Camera
Hard Specification	Screen size	-	-
	Operating voltage	5V / 2A; 12-24V DC	DC 5V
	Current Consumption	320mA	110mA
	Super Capacitor	Yes	-
	Button	Tact	-
	Wireless Link	Yes	-
	Microphone	Built-in	-
	Speaker	Built-in	-
	GPS Receiver	Built-in	-
	G-sensor	Built-in	-
	Collision sensitivity	-4.0G to +4.0G (0.1G Step)	-
	Image sensor	1/2.8 CMOS sensor	1/2.8 CMOS sensor
	Valid Pixel	5.14M Pixels(2616 x 1964)	2.12M Pixels(1936x1097)
	Number of Pixel	3.7M Pixels (2560 x 1440)	2M Pixels(1920x1080)
	Angles of view	Horizontal : 114° Vertical : 82° Diagonal :154°	Horizontal : 129° Vertical : 66° Diagonal :161°
	Lens rotation	Yes	Yes(180°)
	Image reversal (Upside down)	Yes	-
	Lens	F1.8	F2.0
	Polarization Filter	Bundled	No
	Operating temperature	-10°C to +60°C	-10°C to +60°C
	Noise Protection	Yes	Yes
OSD Menu Language	Implemented languages	EN/DE/FR/NL/IT/ES/PT/RU/PL/CZ/RO	-

		Front Camera	Rear Camera
Hard Specification	Screen size	-	-
	Operating voltage	5V / 2A; 12-24V DC	DC 5V
	Current Consumption	320mA	110mA
	Super Capacitor	Yes	-
	Button	Tact	-
	Wireless Link	Yes	-
	Microphone	Built-in	-
	Speaker	Built-in	-
	GPS Receiver	Built-in	-
	G-sensor	Built-in	-
	Collision sensitivity	-4.0G to +4.0G (0.1G Step)	-
	Image sensor	1/2.8 CMOS sensor	1/2.8 CMOS sensor
	Valid Pixel	5.14M Pixels(2616 x 1964)	2.12M Pixels(1936x1097)
	Number of Pixel	3.7M Pixels (2560 x 1440)	2M Pixels(1920x1080)
	Angles of view	Horizontal : 114° Vertical : 82° Diagonal :154°	Horizontal : 129° Vertical : 66° Diagonal :161°
	Lens rotation	Yes	Yes(180°)
	Image reversal (Upside down)	Yes	-
	Lens	F1.8	F2.0
	Polarization Filter	Bundled	No
	Operating temperature	-10°C to +60°C	-10°C to +60°C
	Noise Protection	Yes	Yes
OSD Menu Language	Implemented languages	EN/DE/FR/NL/IT/ES/PT/RU/PL/CZ/RO	-