



5010 Chestnut Oak


	US Units	Metric Units
Style Number	2024V	
Construction	SPC	
Profile	Fold-N-Tap	
Size	9" x 59"	22.86 cm x 149.86 cm
Overall Thickness	0.256"	6.5 mm
Wear Layer Thickness	20 mil (0.02")	0.5 mm
Attached Underlayment	EVA Pad	
Attached Underlayment Thickness	0.059"	1.5 mm
Finish	ScuffResist	
Edge Description	Bevel	
Area per Carton	21.79 sq ft	2.02 sq m
Area per Pallet	1394.56 sq ft	129.56 sq m
Installation	Floating	
Installation Grade	Above, On, Below	
Color Variation	Yes	
Ortho-Phthalates Free	Yes	
Embossed In Register	Yes	
Residential Warranty	Lifetime	
Commercial Warranty	10 Year Light Commercial	

Colors







Coordinating Trim

					
Baby Threshold*	T-Molding*	Multi-Purpose Reducer	Quarter Round	Overlap Stairnose	Flush Stairnose
BT3HS 94"	TM3HS 94"	VSMP6 94"	VSQT6 94"	VSST6 94"	VFSN3 94"
VSBTB 94"	VSTM6 94"				

*Packaged with molding track

Coordinating Metal Trim

			
Finish	Reducer	T-Mold	Stair Cap
Satin Silver	134SA	137SA	131SA
Satin Nickel	135SA	138SA	132SA
Dark Bronze	136SA	139SA	133SA

Installation Range

Profile Size	Installation Range
3.5mm	1.5mm to 3.5mm heights
5.5mm	3.6mm to 5.5mm heights
8mm	6mm to 8mm heights



TREADZ®

Center	LVCTR
Right	LVCAR
Left	LVCAL
White Riser	LVWRI*

*packages of 3