





# 570 CFM/12.5 SONES @ 0.10" SP.

**Dimensions** 

Overall bottom projection - 235/8" Height (less chimney) - 12<sup>1</sup>/<sub>2</sub>" Available widths: 35<sup>1</sup>/<sub>2</sub>"

## **Hood Body**

Brushed stainless steel with tempered glass.

#### Motor

3 speed, permanently split capacitor motor. Rated 120 volts, 60 hz.

### Lighting

Four - GU10 base, MR16, 50 watt halogen lights.

#### **Ducting Options**

Vertical ducting: 6" round duct adapter complete with polymetric back draft damper ensuring quiet operation. Ductless: Requiers charcoal filter (not included).

### **Blower Wheel**

Dual inlet, electronically balanced polymetric centrifugal blower wheel, 53/4" width 59 paddles.

Ceiling mounted with included mounting bracket. Install 20" to 30" from cooking surface.

Grease Filter: BCGF-01 (included). Charcoal Filter: BCCF-01 (not included).

#### **Available Finishes**

Stainless Steel.





351/2"

235/8"

EXPANDED PERFORMANCE												
	Static Pressure (inches of w.g.)						Sones	Fan Speed	Power			
	0	0.1	0.25	0.5	0.75	1.0	@ .1 SP	RPM	Watts	Amps		
Air Flow - CFM	589	570	549	524	504	479	12.5	2560	502.0	2.8		

PROJECT							ARCHITECT			
LOCATION							ENGINEER	ENGINEER		
CONTRACTOR							SUBMITTED BY		DATE	
FAN NUMBER	MODEL NUMBER	CFM	IN W.C.	RPM	WATTS	AMPS	SONES	QTY	OPTIONAL EQUIPMENT & REMARKS	



U.S.: 820 Lincoln Avenue West Chester, Pennsylvania 19380-4466 Tel: (610) 692-7400 • 877-304-3785 Fax: (610) 696-8048

Canada: 8 Edvac Drive Brampton, Ontario L6S 5P2 Tel: (905) 456-2033 • 800-250-8767

Fax: (905) 456-1015

Updated 2-13 Specifications subject to change without notice.