



Powered by the exclusive **iQ Blower System™ with GPS Technology** (see page 62) for the quietest, most energy efficient and fastest smoke and odor removal available in a range hood; external blowers offered separately.

Mesh lined Hi-Flow™ baffle filters provide superior grease capture to ensure a clean, fresh kitchen.

Works with optional Universal Make-Up Air Dampers.

Heat Sentry™ detects excessive heat and adjusts blower speed to high automatically.

Model Numbers:

PK2230

PK2239

PK2245

PKEX2239

PKEX2245



Integrated electronic controls include delay-off to continue ventilation after cooking and filter clean reminder to keep the kitchen smelling fresh.



Halogen lights provide brilliant 3-level cooktop lighting.



Use the calibration button to activate GPS Technology (see page 62).



Protect cabinetry from steam and grease with stainless steel liners that provide a custom fit.



Optional ACR2 remote control lets the busy cook stay in control from anywhere in the kitchen.



Hood Sizes

Widths 27-3/4", 36-1/2", 43-7/16"

Depth 15-7/16"

Finish

Stocked Brushed Stainless Steel

Special Order Not Available

Features

Lighting Type Halogen 50W, GU10

Number of Lamps 2 on 27" and 36"
3 on 43"

Lighting Levels 3

Lighting Lamps Included Yes

Control Type 3-speed Plus Boost Electronic Pushbutton

Control Features Heat Sentry™, Delay Off, Filter Clean Reminder

Remote Control Optional ACR2

Filter Type Hi-Flow™ Baffle Filter

Non-ducted Capability No

Hood Blower Included (PK22)

Internal	iQ12
Blower CFM	1200
Sones Low/High	
PK2230	0.6/11.5
PK2239	0.6/11.5
PK2245	0.6/11.0

Hood Blower Options (PKEX22 blowers sold separately)

External In-line	ILB3	ILB6	ILB9	ILB11
Max CFM	280	600	800	1100
Some levels are typically half of comparable CFM internal blowers.				
External Exterior (sold separately)	EB6	EB9	EB12	EB15
Max CFM	600	900	1200	1500
Some levels are typically half of comparable CFM internal blowers.				

Accessories

Liners: Optional AL3036, AL3042, AL3948, AL3954, AL4554, AL4560

Light Panel for Liners: Optional ALP36, ALP42, ALP48, ALP54, ALP60

Universal make-up air damper MD6TU, MD8TU or MD10TU

Optional Transition 10" to 8" Reducer Model 472

Installation Requirements


Amps @ 120V 8.0 for PK2230, PK2239; 8.5 for PK2245

Electrical Direct Wire

Duct Size 10"

Duct Direction Vertical

Backdraft Damper Included



Installation height above the cooking surface: 24"-30"

For more details see the product specifications sheet found at www.BESTRangeHoods.com