



# Bowers & Wilkins

**603 S3**

Technical Information



**Technical features**

Decoupled Double Dome Titanium tweeter  
Continuum™ cone FST™ midrange  
Paper bass cones  
Flowport™

**Description**

3-way vented-box system

**Drive units**

1x ø25mm (1 in) Titanium Dome high-frequency  
1x ø150mm (6 in) Continuum cone FST midrange  
2x ø165mm (6.5 in) Paper bass cone

**Frequency range**

-6dB 29Hz - 33kHz

**Frequency response**

(+/-3dB from reference axis)

46Hz - 28kHz ±3dB

**Sensitivity**

(on axis at 2.83Vrms at 1m)

90dB

**Harmonic distortion**

2nd and 3rd harmonics (90dB, 1m on axis)  
<1% 100Hz - 22kHz  
<0.5% 350Hz - 12kHz

**Nominal impedance**

8Ω (minimum 3.0Ω)

**Recommended amplifier power**

30W - 200W into 8Ω on unclipped programme

**Max. recommended cable impedance**

0.1Ω

**Dimensions**

Height: 985 mm (38.8 in) cabinet only  
1,020 mm (40.2 in) including plinth  
Width: 190 mm (7.5 in) cabinet only  
260 mm (10.2 in) including plinth  
Depth: 340 mm (13.4 in) cabinet only  
368 mm (14.5 in) including grille and terminals  
402 mm (15.8 in) including plinth

**Net weight**

27.5kg (60.6lbs)

**Finishes**

Cabinet: Black  
White  
Oak  
Red Cherry (APAC only)

Grille: Black (Black and Red Cherry)  
Grey (White and Oak)