

UP60W



Colour range

Body



Blue grey – BG



White – WH



Stainless steel – SS



Graphite matt – MG



Glossy black – BK

RAL

Optional RAL – RA

Finishes

Knobs, handles



Satin

Optional solid door version

Order code: change letter “W” with “Q”

Available ovens

Electric oven

Primary oven:
UOV 80 M


Maximum input:
3.7 kW

Secondary oven:
UOV 60 M


Maximum input:
3.5 kW

Configurations

7 burners with fry top* and coup de feu



9 burners with fry top*



Electric oven

UP60FSWMP

Brushed

UP60FWMP

Brushed







Fuel requirements

Natural gas / Liquid propane
Voltage: 240 Volts
Amps: 30

Natural gas / Liquid propane
Voltage: 240 Volts
Amps: 30

**Insufficient amperage may lower heating performance when multiple functions are being used at the same time*

Consumption

 Coupe de Feu 5500 btu/h	 Double ring Dual burner 25000 btu/h / 900 btu/h	 Griddle 10500 btu/h / 2000 btu/h + 7000 btu/h / 1400 btu/h	 Oval burner 10500 btu/h / 3100 btu/h	 Big burner 10500 btu/h / 2000 btu/h	 Small burner 7000 btu/h / 1400 btu/h
---	--	--	--	---	--

Complements & accessories

Hood

UAGQ60

Ladle holder panel

AM4-150

Technical drawing & dimensions

