Specifications

	6301ND	6301NX	6301NE	6301NB
Type	Sealed powered speaker system			
Speaker	100 mm cone-shaped, full-range speaker × 1			
Frequency band	70 Hz to 15 kHz			
Output sound pressure level	85 dB/W (1 m)			
Maximum output sound pressure level	98 dB			
Rated output	20 W			
T. H. D.	0.05% (at 1 kHz 1 W output)			
Input terminal	Analog unbalanced/ϕ6.3 mm (1/4") TS phone			
	Digital XLR-3-31 type IEC60958 (AES/EBU) sampling frequency 44.1 kHz to 96 kHz	Analog balanced XLR-3-31 type HOT No. 2/ transformer type	Analog balanced XLR-3-31 type HOT No. 2/ electronic type	—
Output terminal (THRU)	Digital XLR-3-32 type	—		
Input impedance	Analog input (balanced/unbalanced) 10 kΩ or more			
Input sensitivity	Analog (unbalanced): -14 dBV (0.2 Vrms) Digital: -12 dBFS	Analog (unbalanced): -14 dBV (0.2 Vrms) Analog (balanced): +4 dBu (1.2 Vrms)		Analog (unbalanced): -14 dBV (0.2 Vrms)
Residual noise	–65 dBV	–70 dBV		
Enclosure material	Aluminum die-casting			
Power consumption	10 W			
External dimensions (mm)	120 (W) × 189 (H) × 120 (D)			
Weight	Approx. 2.3 kg			
Length of the power cord	Approx. 2 m			