

Specs & Details

Dimensions: 68 1/4 H x 24 W x 24 D

APPEARANCE

| | |
|--------------------------------|-----------------------------|
| <u>Color Appearance</u> | <u>Gray</u> |
| <u>Installation</u> | <u>Free-Standing</u> |

CAPACITY

| | |
|-----------------------------|--------------------------|
| <u>Unit Capacity</u> | <u>50 Gallons</u> |
|-----------------------------|--------------------------|

ECONOMICAL / QUIET

| | |
|-------------------------------------|----------------------|
| <u>Operating Sound Level</u> | <u>41 dBA</u> |
|-------------------------------------|----------------------|

FEATURES

| | |
|---------------------------------------|---|
| <u>Anode Rod</u> | <u>Sensing Magnesium</u> |
| <u>Communication</u> | <u>Yes</u> |
| <u>Connected Capabilities</u> | <u>Amazon Alexa Google Home</u> |
| <u>Control Type</u> | <u>Electronic LED Service Diagnostics Integrated</u> |
| <u>Demand Response Capable</u> | <u>Yes</u> |

| | |
|---|--|
| <u>Diagnostic Feedback</u> | <u>Filter, Lock, Standard Electric</u> |
| <u>Drain Valve</u> | <u>Left Side</u> |
| <u>Drain Valve Type</u> | <u>Brass</u> |
| <u>Electronic, Integrated Mixing Valve</u> | <u>Yes</u> |
| <u>Fuel Type</u> | <u>Electric</u> |
| <u>Operating Modes</u> | <u>Hybrid (Default Mode)</u> <u>Heat Pump</u> <u>High Demand/Boost</u> <u>Standard Electric</u> |
| <u>Power Cord Length</u> | <u>6' 3-prong</u> |
| <u>Product Type</u> | <u>Electric Heat Pump</u> |
| <u>Renewable Air Filter</u> | <u>Top of Unit</u> |
| <u>Sensor</u> | <u>Leak Sensor Included (SPLK10N01A)</u> |
| <u>Temp & Pressure Relief Valve</u> | <u>Right Side</u> |
| <u>Temperature Setting</u> | <u>100-140° F Range</u> |
| <u>Temperature Setting Factory Default</u> | <u>120° F</u> |

| | |
|---|------------------------|
| <u>UEF</u> | <u>3.2</u> |
| <u>Water Connection Location</u> | <u>Top</u> |
| <u>WiFi Connect</u> | <u>Built-In</u> |

POWER / RATINGS

| | |
|--|---|
| <u>Electrical Circuit Required</u> | <u>120/110VAC 15A, 60HZ or 240/208VAC 25A, 60Hz</u> |
| <u>Electrical Consumption - Lower Element</u> | <u>3600W at 240VAC</u> <u>900W at 120VAC</u> |
| <u>Electrical Consumption - Upper Element</u> | <u>3600W at 240VAC</u> <u>900W at 120VAC</u> |
| <u>Energy Consumption (kWh/year)</u> | <u>1015</u> |
| <u>First Hour Rate (FHR)</u> | <u>59 Gallons</u> |
| <u>Hertz</u> | <u>60</u> |
| <u>Operating Water Pressure</u> | <u>20-125 PSI (30-80 PSI recommended)</u> |

WARRANTY

| | |
|------------------------------|---|
| <u>Labor Warranty</u> | <u>Limited 1-year entire appliance</u> |
| <u>Parts Warranty</u> | <u>Limited 10-year tank and parts</u> |

WEIGHTS & DIMENSIONS

| | |
|---|-------------------------|
| <u>Approximate Shipping Weight</u> | <u>195 lb</u> |
| <u>Connection Sizes - Hot Water Outlet (MNPT)</u> | <u>3/4"</u> |
| <u>Connection Sizes - Water Inlet (MNPT)</u> | <u>3/4"</u> |
| <u>Net Weight</u> | <u>179 lb</u> |
| <u>Overall Depth</u> | <u>24 in</u> |
| <u>Overall Height</u> | <u>68 1/4 in</u> |
| <u>Overall Width</u> | <u>24 in</u> |
| <u>Product Diameter</u> | <u>24 in</u> |
| <u>Product Height (to top of unit)</u> | <u>66 1/2 in</u> |
| <u>Product Height (to top of water inlet/outlet connections)</u> | <u>68 1/4 in</u> |