







shawfloors.com

OCALA



	US Units	Metric Units		
Style Number	SW590			
Construction	Engineered			
Species	Maple			
Nominal Overall Thickness	3/8"	8.2 mm		
Nominal Width	5" 127 mm			
Finish	ScufResist Platinum			
Gloss Level	40%			
Surface Texture	Smooth			
Edge Description	Pillowed			
End Description	Pillowed			
Profile	Tongue And Groove			
Weight per Carton	35 lbs	15.87 kg		
SQFT per Carton	23.66 sq ft	2.19 sq m		
SQFT per Pallet	1419.6 sq ft	131.88 sq m		
Installation Methods	Nail, Staple, Glue, Floating			
Installation Grade	Above, On, Below			
Variation	Moderate			
GREENGUARD® Certified	Yes			
Cradle-to-Cradle Certified	Yes			
Radiant Heat Approved	Yes			
Residential Warranty	Lifetime			
Commercial Warranty	5 Year Commercial			
All measurements are nominal.	Cartons may include random lengths.			

Features

The smooth surface of Ocala is sophisticated and refined - perfect for urban and contemporary settings. Also available in a scraped surface version, Clearwater.

Suggested Adhesive

Style Name	Style Number
35MC	HS105
Urebond Plus	SWADH

Trim Pieces length: 78" (*Overlap Reducer and Overlap Stairnose are designed for floating installations only. These items are nonstocking - but are available through a quick-ship program. Delivery should take approximately 2 to 3 weeks.)



Contact the Shaw Information Center for additional details: 800-441-7429.





OCALA



Colore				
			529 Oceanside	627 Burnside
698 Conway	1023 Crescent Beach	5034 Windsurf		

