



DF481761F
400 series dishwasher
fully integrated
with flexible hinge
Appliance height 86.7 cm / 34 1/8 "

8 programs with aqua sensor and 4 cycle options such as Power, Intensive, Half Load and Extra Dry
Flexible rack system with smooth running rails on all levels and a soft-closing system of the upper and lower rack
TFT display for intuitive operation of all functions
Perfectly illuminated interior
Push-to-open function for a seamless integration into handleless furniture fronts
Very quiet: 41 dB
ENERGY STAR® certified
Aqua stop

Operation

TFT display indicating remaining or end time, refill for salt and rinsing agent, inflow of water.
 Touch key operation.
 Information key with use indications.
 Sanitized indicator in the control panel.
 Delayed start timer up to 24 hours.
 Visual and acoustic end of program indicator.
 Info-Light.

Technical features

Perfectly illuminated interior.
 Glass protection.
 Aqua sensor.
 Load sensor.
 Automatic detergent function.
 Regeneration electronics.
 Flow-through water heater.
 Triple filter system, self-cleaning.
 Soft lock.
 Aqua stop.

Programs

8 programs:
 Auto 113 °F - 122 °F.
 Auto 130 °F - 150 °F.
 Auto 150 °F - 160 °F.
 Standard Eco 122 °F - 131 °F.
 Wash and Dry.
 Quick Wash 113 °F (29 min.).
 Glass Care 122 °F.
 Pre-rinse.
 4 cycle options:
 Intensive.
 Power.
 Half Load.
 Extra Dry.

Features

Flexible rack system with smooth running rails on all levels and a soft-closing system on the upper and lower rack.
 3rd rack for cutlery.
 Upper rack:
 Over extension.
 Rackmatic with 3 levels, adjustable in height up to 2".
 6 folding tines.
 4 folding racks.
 2 glass support bars.
 Lower rack:
 8 folding tines.
 2 folding racks.
 Dividable glass support.
 Cutlery basket.
 Holder for long-stemmed glasses.
 Maximum dish sizes (upper/lower basket) 9"/11", 8"/12" or 7"/13" respectively.
 13 place setting capacity.
 Maximum glass loading capacity 23 wine glasses.

Product Features

Watts (W)
1300
Current (A)
12
Volts (V)
120
Frequency (Hz)
60
Power Cord Length
47 1/4"
Minimum Water Pressure (lb/sin)
7.0
Length inlet hose (in)
55 1/8"
Length outlet hose (in)
55 1/8 "
Overall appliance dimensions (HxWxD) (in)
34 1/8 " x 23 9/16 " x 21 5/8 "
Required cutout size (HxWxD) (in)
x 34 1/8 " x 23 9/16 "
Adjustable feet
Yes

Consumption and connection features

Number of wash cycles
4
Number of options
8
Third Rack
3rd Rack 2.1
Tube material
Stainless steel
Concealed heating element
Yes
Leak protection system
24/7 Aqua Stop Plus
Five-level wash
Yes
Water softener
Yes
ChildLock
Yes
Total annual energy consumption (kWh)
259
Energy Efficiency Class
Tier 1
Energy Star® qualified
Yes
Total annual energy consumption (kWh)
623.5
Total annual water consumption (g)
624
Number of place settings
13
2018-02-05
Page 1

Consumption data

Total annual energy consumption 259 kWh.
 Water usage 2.5 gallons
 Noise level 41 dB.

Planning notes

Height-adjustable feet.
 Appliance toe kick recess 3 15/16".
 Rear feet adjustable at front.
 Door weight up to 22 lbs.
 Door panel dimension dependent on toe kick height of kitchen cabinets.
 Installation and usage also with furniture handle possible. The push-to-open function remains active.
 Ventilation openings required when installed as a tall unit.

Rating

Total rating 1.3 kW.
 Connecting cable 47 1/4" plugable.
 Water connection with 3/4" screw gland.
 Connection to hot or cold water possible.

Color Variants

DF481761F
fully integrated
with flexible hinge

Included accessories

1 x baking tray spray head.
 1 x GN container insert.
 1 x glass holder rack.

Optional accessories

DA042030
Sterling silver cutlery cassette
DA043000
Holder for long-stemmed glasses

Installation Accessories

DA020110
Stainless steel trim kit for tall tub dishwashers
GZ010011
Extension for inlet and outlet (78" long)

DF481761F
400 series dishwasher
fully integrated
with flexible hinge
Appliance height 86.7 cm / 34 1/8 "
2018-02-05
Page 2

Dishwasher (34 1/8" (86.7 cm)) with flexible hinge

