



# SBC58BLIFFLTWADALHD



32" x 23.63" x 22.38" (H x W x D)

Built-in 24" wide ADA-compliant dual tap beer dispenser with panel-ready door and removable tap system for non-permanent installation

**Highlights:**

Innovative Floating Tap lets you create a complete undercounter kegerator without modifying your countertop

Easy-to-install + removable tap system allows you to change your space as needed

Just 32" high for an easy fit under lower ADA compliant counters

**Product Features:**

24" Wide Built-In Floating Tap Beer Dispenser	Dual tap kegerator with a remote tapping system that includes everything you need to pour draft beer without modifying your countertop
Commitment-free design	Non-permanent draft tower is separated from the actual kegerator and designed for temporary installation on counter surfaces, allowing you to remove as needed
ADA compliant design	32" height allows easy installation under lower ADA compliant counters
Built-in capable	Designed for installation under the counter
No drilling needed	Tower is connected to the removable tap kit that does not need to be permanently attached to your countertop
Panel-ready door	Integrated stainless steel door frame allows you to mount full overlay panels over the door to create a custom look that can blend into cabinetry with no exposed frame (panel size: 23 5/16" W x 28 1/4" H and at least 3/4" thick; maximum weight: 10 lbs.)
Dual tap system	Twin draft tower allows you to serve from two 1/6 (sixtel) sized kegs
Easy installation	No tools or equipment needed for fast setup and easy removal
Convertible to a refrigerator	Includes a tap hole cover, glass shelves, and a scalloped steel bottle rack to all you to convert the kegerator into a traditional all-refrigerator



## SBC58BLIFFLTWADALHD Specifications:

Overview	
Nominal Width	24.0" (61 cm)
Nominal Height	32.0" (81 cm)
Height of Cabinet	31.88" (81 cm)
Height to Hinge Cap	32.0" (81 cm)
Width	23.63" (60 cm)
Depth	22.38" (57 cm)
Depth with Handle	24.3" (62 cm)
Depth with door at 90°	44.5" (113 cm)
Capacity	5.8 cu.ft. (164 L)
Defrost Type	Automatic
Door	Panel-Ready
Cabinet	Black
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S
Energy Usage/Year	239.0kWh/year
Amps	0.8
Voltage/Frequency	115 V AC/60 Hz
Weight	180.0 lbs. (82 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101146003
Kegerator	
Door Swing	LHD
Height Adjustable	No
Tap Kit	Yes
Number of Taps	2
Adjustable Shelves	Yes
Shelf Type	Glass and Scalloped
Shelf Qty	4
Thermostat Type	Dial
Interior Light	Yes
Refrigerant	R600a
Refrigerant Amount	0.64 oz.
Inter Height	27.0" (69 cm)
Interior Width	21.0" (53 cm)
Interior Depth	17.75" (45 cm)

Compressor Step Height	6.5" (17 cm)
Compressor Step Width	21.0" (53 cm)
Compressor Step Depth	5.5" (14 cm)
Level Legs Qty	4
Temperature Range	36 to 46°F

No  
Countertop  
Drilling

