


- The Captur[™] system's advanced blower design features a forward positioned centric inlet to remove smoke and odor faster. Three-speed blower control exhausts at 300 CFM.
- Smooth-flow blower wheel design and high flow filters ensure quiet,
 1.2 sone operation at normal speed.
- Bright, two-level LED modules supported by a 3-year warranty illuminate evenly and are tested in cooking environments to ensure long life without dimming.
- Tap-touch, 3-speed capacitive control features a smooth, easy-to-clean surface.
- Dishwasher-safe, micro-mesh filters provide efficient grease removal.
 The filter clean reminder ensures they will always maintain a high level of capture.
- EZ1 brackets make it easy for singleperson installation in less than half the time of traditional methods.
- ADA compliant, remote operation is possible using a standard UL approved wall switch (kit sold separately).
- Non-duct capable with use of charcoal filters, sold separately. Hidden louvers on top of hood exhaust away from cabinetry.



SPECIFICATIONS

OPTIONAL ACCESSORIES

Width	Blower CFM	Normal Sones	Volts	Amps	Duct	Non-Ducted Charcoal Filter	ADA Electronic Adapter Kit*
30"	300	1.2	120	.65	3-1/4" x 10" or 7" RD	HPF30 (Type Xc)	HAWRK3
36"						HPF36 (Type Xd)	
42"						HPF42 (Type Xe)	

^{*} Kit sold separately.