

K750GT Gaucho Freestanding Grill



PRODUCT FEATURES

- Wood-fired grill with motorized rotisserie spit that raises and lowers above the fire; motor mounted in cabinet
- 33" x 22" (726 square inches) of primary grilling surface
- Two powerful gas burners to start the wood fire, 24,000 BTUs each (LP)
- · Natural gas or bulk liquid propane
- · Safety valves for every burner and electronic control bezels with flame sensor LED indicators
- Deep hopper cleanout
- Two side shelves
- Optional laser-cut grilling surfaces available with your choice of patterns optimized for cooking meat, fish, and vegetables
- Optional Argentinian-style V-grates with drippings trays
- · Marine-grade stainless steel available

Overall Width / Installation Width	82.63 in (2100 mm)
Overall Depth / Installation Depth	32.13 in (817 mm)
Overall Height / Counter Height	78.75 in (2000 mm) / 36 in (915 mm) +/- 1 ¼ in (33 mm)
Approximate Product Weight	540 lb (245 kg)
Gas Requirements	Natural Gas: 1/2" male NPT connection. 10 ft. (305 cm) gas hose with quick
	disconnect provided. Gas service line to deliver 7 i.w.c. at grill location. See BTU
	information below for pipe sizing.
	Bulk Propane: 1/2" male NPT connection. 10 ft. (305 cm) gas hose with quick discon-
	nect provided. Gas service line to deliver 11 i.w.c. at grill location. See BTU informa-
	tion below for pipe sizing.
	Propane Cylinder: Not available
Electrical Requirements	120VAC/60Hz Includes 1 ff. (30.5 cm) 3-prong grounded power cord.
Maximum AMP usage	3 amps
Total BTUs	48,000 BTU liquid propane / 45,000 BTU natural gas

Ensure proper gas pipe sizing. Diameter and length of the supply pipe may limit the pressure and BTU delivery.

For outdoor use only. Maintain at least 36 inches (915 mm) of clearance between the sides and back of the grill and any combustible surface. Never place the grill underneath an overhead combustible structure or surface. High altitude kit available.



K750GT Gaucho Freestanding Grill





