

Product data sheet

HEATING TYPE

Heating type	Induction
--------------	-----------

CONSTRUCTION TYPE

Independent of oven	•
---------------------	---

DESIGN

Elegant glass ceramic surface	•
Ceramic surface colour	Black
Stainless-steel frame	•
Surface-mounted installation	•

COOKING ZONE DETAILS

Number of cooking zones	4
Number of cooking areas	0
Maximum number of pans	4

USER CONVENIENCE

Operation via sensor controls	Smart Select
Display colour	Yellow
Pan and pan size recognition	•
Constant pan recognition	•

Recall function	•
Stop & Go function	•
Timer	•
Safety shut-off	•
Auto heat-up	•
Keeping warm	•
Individual setting options (e.g. audible signal tones)	•
Networking with Miele@home	•
Con@ctivity 3.0 automatic function	•

CLEANING CONVENIENCE

Easy-to-clean ceramic glass	•
------------------------------------	---

SAFETY

Safety shut-off	•
Safety lock	•
System lock	•
Integrated cooling fan	•
Overheating protection	•
Residual heat indicator	•

TECHNICAL DATA

Dimensions in mm (width)	30 5/8 (775)
Installation height incl. connection box in mm	2 7/8 (71)
Dimensions in mm (depth)	21 1/2 (544)

Cutout dimension in mm (width) with surface-mounted installation	28 5/8 (724)
---	--------------

Cutout dimensions in mm (depth) with surface-mounted installation	20 1/2 (518)
--	--------------

Weight in lbs (kg)	37 (17)
---------------------------	---------

Total rated load in kW	6.600-7.600
-------------------------------	-------------

Voltage in V	0
---------------------	---

Frequency in Hz	60
------------------------	----

Dimensions in mm (height)	3 1/8 (78)
----------------------------------	------------

ACCESSORIES SUPPLIED

Power cable	•
--------------------	---

1ST COOKING ZONE / COOKING AREA

Position	front left
-----------------	------------

Type	Dual-circuit ring
-------------	-------------------

Max. rating in W	2600
-------------------------	------

Max. booster rating in W	3000
---------------------------------	------

Size in mm	Ø 180–280
-------------------	-----------

Max. TwinBooster rating in W	3,700
-------------------------------------	-------

2ND COOKING ZONE / COOKING AREA

Position	rear left
-----------------	-----------

Type	Dual-circuit ring
-------------	-------------------

Max. rating in W	1400
-------------------------	------

Max. booster rating in W	1700
---------------------------------	------

Max. TwinBooster rating in W	2200
-------------------------------------	------

Size in mm

100-160 mm

3RD COOKING ZONE / COOKING AREA

Position	rear right
Type	Dual-circuit ring
Size in mm	Ø 140–190
Max. rating in W	1850
Max. booster rating in W	2500
Max. TwinBooster rating in W	3000

4TH COOKING ZONE / COOKING AREA

Position	front right
Type	Dual-circuit ring
Size in mm	Ø 140–190
Max. rating in W	1850
Max. booster rating in W	2500
Max. TwinBooster rating in W	3000