30" DUAL FUEL PROFESSIONAL RANGE

F4PDF304S1



Heavy Duty Grates



Continuous Grate Surface



Dual Crescendo Burner



Dual Convection



Self Clean Oven



Multi-level cooking



Cool Touch Door



Digital Controls



Fast Pre-Heat



COLOR KIT



OPTIONAL ACCESSORIES

ACDKIT30 ... Color kit **FMWOK** Wok ring **FMSIM** Simmer plate F6BG30BCI Island trim F6BG30STD Standard trim F6BG30HBT High back trim FMGRID30 Griddle FMTRP30 Telescopic rack

COOKING SURFACE

2 Heavy Duty, continuous cast iron grates
One piece, matte finish porcelain burner bowl
2 Dual-Flame Crescendo Burners
2 X 18,000 BTU max (NG)
2 Rapid Burners
2 X 15,000 BTU max (NG)
Natural Gas (LP convertible)

OVEN

Dual True Convection
Self-cleaning oven with Multifunction baking
Black Porcelain enamel interior
Cool to the touch door
Extra-large baking cavity and viewing area
3 Halogen lights for flawless visibility
Gross capacity 4.4 cu. ft.
2 chromed racks
Enameled Broiler Pan


OVEN FUNCTIONS

Bake
Broil
Roast
Convection
True Convection
Warm / Proof / Dehydrate
Electronic cooking programmer
Fast Pre-Heat
Self-Clean
Sabbath Mode

ACCENTO

30" DUAL FUEL RANGE





CODE ID	F4PDF304S1 - 30" DUAL FUEL PROFESSIONAL RANGE				
Series and Finish	400 Carias - Professional Degian - Stainless Stael				
CONTROL PANEL	400 Series - Professional Design - Stainless Steel				
Control Type	6 Heavy Duty Knobs				
Display: Clock - Temperature - Function	White LED				
COOKTOP		Willie LEB			
Cooking Surface		Black Enameled			
Type	GAS (NG or LP)				
GAS COOKTOP FEATURES		and (ita di Ei)			
	Electric Flame Ignition and Re-ignition	L.P. Conversion Kit	Top Mount Injectors		
	Flame-out sensing	Dual Crown Brass Burner	Pressure Regulator		
Cooking Zones	Tiamo car conomig	4	1 Toobard Trogulator		
Burners Type	Rapid Burner				
Power Front-L, Rear-R (Max/Min) G20 - 5" (NG)	15000 (BTU/h) - 4400W / 2200 (BTU/h) - 645W				
Power Rear-L, Front-R (Max/Min) G20 - 5" (NG)	18000 (BTU/h) - 5300W / 950 (BTU/h) - 275W				
Power Front-L, Rear-R (Max/Min) G31 - 10" (LP)	12000 (BTU/h) - 3500W / 2200 (BTU/h) - 645W				
Power Rear-L, Front-R (Max/Min) G31 - 10" (LP)	15000 (BTU/h) - 4400W / 950 (BTU/h) - 275W				
OVEN	Electric Pyro				
Туре	Multifunction 2 Fans				
Temperature Regulation	Electronic				
OVEN FUNCTIONS	Power Rear-L, Front-R				
	Pyrolytic Self-Clean with automatic door latch	Pizza (Lower Convection)	Proof (Warm)		
	True European Convection Bake (Multilevel)	Bake	Broil		
	Dehydrate	Thaw (Defrost)	Convection Broil		
	Convection Roast	Oven Lights	Keep warm (Warm Plus)		
ELECTRIC OVEN FEATURES					
	Preset/Last Used	Preheat Indicator	Automatic Fast Preheat		
	Temperature Memory	(25%, 50%, 75%, 100%)			
	Child Door Lock	Sabbath Mode	Hour Clock Formats AM / PM		
	°F Degree unit				
OVEN DOOR(S)					
Oven Glass Window	Deep Embossed Window				
Door Cooling System	4 Pane Heat Resistant Glasses Heavy Duty Steady Tilt				
Door Hinges Handle Style	Heavy Duty Steady Tilt Stainless Steel Tube d30mm with Metal terminals				
OVEN CAVITY	Stairile	ess Steer Tube domini with Metar te	erminais		
Net Capacity (cbft)		4.4			
Cavity Enamel Colour	Black				
Rack Positions	6				
Oven Lights	3x20W Halogen				
HEATING ELEMENTS (@240V)		CALOTT HAIOGOIT			
Broil Upper Heating Element		3500 W (240V)			
Upper Auxiliary Element Wattage	1032 W (240V)				
Concealed Bake Lower Heating Element	3000 W (240V)				
Convection Element	2 x 1300 W (240V)				
OVEN ACCESSORIES		,			
Chromed Racks		2 rack without frontal bend			
Enameled Grill set (basin + anti splash)	1				
Telescopic Chromed Rack	Only as optional ACCESSORY				
Meat Probe	Only as optional ACCESSORY				
DIMENSIONS/WEIGHT (In or Lbs)					
Overall dim - Width	29 - 3,	,	'58 mm)		
Overall dim - Height (min - max)	39"		993 mm)		
Overall dim - Depth	29 - 3	/4" (7	756 mm)		
POWER / RATINGS (208/240 V, 60 HZ)					
	3.84 kW - 16.9Amps				
kW / Amps rating at 120-240V, 60Hz			3.54 kW - 17.5Amps		
kW / Amps rating at 120-240V, 60Hz kW / Amps rating at 120-208V, 60Hz					
kW / Amps rating at 120-240V, 60Hz kW / Amps rating at 120-208V, 60Hz Power Cable		3.54 kW - 17.5Amps Nema 14-50P			
kW / Amps rating at 120-240V, 60Hz kW / Amps rating at 120-208V, 60Hz					