

Quieting sensitivity	10.2dBf
DIN S/N 46dB	1.13μV / 75Ohms
Frequency response (±3.0dB)	30Hz - 15kHz
S/N (dB)	65dB (MONO)
Selectivity	Over 80dB (±400kHz)
Stereo separation	45dB (1kHz)

AM

Frequency Range (Frequency step)	530kHz - 1700kHz (10kHz)
Usable sensitivity	28dBμ

Video

Color system of external video input	NTSC/PAL
External video input level (Mini jacks)	1 Vp-p / 75 Ohms
External audio max input level (Mini jacks)	2 V / 25 kOhms
Video Input level (RCA jacks)	1 Vp-p / 75 Ohms
Video Output level (RCA jacks)	1 Vp-p / 75 Ohms
Audio Output level (Mini jacks)	0.9 V / 10 kOhms

Audio

Maximum Power Output (Front&Rear)	50Wx4
Typical Power Output (Front&Rear)	Full Bandwidth Power (at less than 1%THD) 22Wx4
Output frequency band	20 - 88,000Hz
Preout level (V)	5V / 10kOhms
Preout impedance (Ω)	≦ 300 Ohms
Speaker Impedance (Ω)	4-8 Ohms

General

Operating voltage	12V DC Car Battery
Maximum Current consumption	15A
Installation Dimensions WxHxD	178mm x 100mm x 155mm 7-3/16 x 4-7/16 x 6-2/16 inch
(with Sleeve)	182mm x 112mm x 153mm 7-3/16 x 4-7/16 x 6 inch
Operational temperature range	-10°C to +60°C
Weight	Main unit 1.7 kg 3.8 lb

Quieting sensitivity	10.2dBf
DIN S/N 46dB	1.13 μ V / 75Ohms
Frequency response ($\pm$ 3.0dB)	30Hz - 15kHz
S/N (dB)	65dB (MONO)
Selectivity	Over 80dB ($\pm$ 400kHz)
Stereo separation	45dB (1kHz)

AM

Frequency Range (Frequency step)	530kHz - 1700kHz (10kHz)
Usable sensitivity	28dB μ

Video

Color system of external video input	NTSC/PAL
External video input level (Mini jacks)	1 Vp-p / 75 Ohms
External audio max input level (Mini jacks)	2 V / 25 kOhms
Video Input level (RCA jacks)	1 Vp-p / 75 Ohms
Video Output level (RCA jacks)	1 Vp-p / 75 Ohms
Audio Output level (Mini jacks)	0.9 V / 10 kOhms

Audio

Maximum Power Output (Front&Rear)	50Wx4
Typical Power Output (Front&Rear)	Full Bandwidth Power (at less than 1%THD) 22Wx4
Output frequency band	20 - 88,000Hz
Preout level (V)	5V / 10kOhms
Preout impedance (Ω)	$\leq$ 300 Ohms
Speaker Impedance (Ω)	4-8 Ohms

General

Operating voltage	12V DC Car Battery
Maximum Current consumption	15A
Installation Dimensions WxHxD	178mm x 100mm x 155mm 7-3/16 x 4-7/16 x 6-2/16 inch
(with Sleeve)	182mm x 112mm x 153mm 7-3/16 x 4-7/16 x 6 inch
Operational temperature range	-10°C to +60°C
Weight	Main unit 1.7 kg 3.8 lb

Quieting sensitivity	10.2dBf
DIN S/N 46dB	1.13μV / 75Ohms
Frequency response (±3.0dB)	30Hz - 15kHz
S/N (dB)	65dB (MONO)
Selectivity	Over 80dB (±400kHz)
Stereo separation	45dB (1kHz)

AM

Frequency Range (Frequency step)	530kHz - 1700kHz (10kHz)
Usable sensitivity	28dBμ

Video

Color system of external video input	NTSC/PAL
External video input level (Mini jacks)	1 Vp-p / 75 Ohms
External audio max input level (Mini jacks)	2 V / 25 kOhms
Video Input level (RCA jacks)	1 Vp-p / 75 Ohms
Video Output level (RCA jacks)	1 Vp-p / 75 Ohms
Audio Output level (Mini jacks)	0.9 V / 10 kOhms

Audio

Maximum Power Output (Front&Rear)	50Wx4
Typical Power Output (Front&Rear)	Full Bandwidth Power (at less than 1%THD) 22Wx4
Output frequency band	20 - 88,000Hz
Preout level (V)	5V / 10kOhms
Preout impedance (Ω)	≦ 300 Ohms
Speaker Impedance (Ω)	4-8 Ohms

General

Operating voltage	12V DC Car Battery
Maximum Current consumption	15A
Installation Dimensions WxHxD	178mm x 100mm x 155mm 7-3/16 x 4-7/16 x 6-2/16 inch
(with Sleeve)	182mm x 112mm x 153mm 7-3/16 x 4-7/16 x 6 inch
Operational temperature range	-10°C to +60°C
Weight	Main unit 1.7 kg 3.8 lb

Quieting sensitivity	10.2dBf
DIN S/N 46dB	1.13μV / 75Ohms
Frequency response (±3.0dB)	30Hz - 15kHz
S/N (dB)	65dB (MONO)
Selectivity	Over 80dB (±400kHz)
Stereo separation	45dB (1kHz)

AM

Frequency Range (Frequency step)	530kHz - 1700kHz (10kHz)
Usable sensitivity	28dBμ

Video

Color system of external video input	NTSC/PAL
External video input level (Mini jacks)	1 Vp-p / 75 Ohms
External audio max input level (Mini jacks)	2 V / 25 kOhms
Video Input level (RCA jacks)	1 Vp-p / 75 Ohms
Video Output level (RCA jacks)	1 Vp-p / 75 Ohms
Audio Output level (Mini jacks)	0.9 V / 10 kOhms

Audio

Maximum Power Output (Front&Rear)	50Wx4
Typical Power Output (Front&Rear)	Full Bandwidth Power (at less than 1%THD) 22Wx4
Output frequency band	20 - 88,000Hz
Preout level (V)	5V / 10kOhms
Preout impedance (Ω)	≦ 300 Ohms
Speaker Impedance (Ω)	4-8 Ohms

General

Operating voltage	12V DC Car Battery
Maximum Current consumption	15A
Installation Dimensions WxHxD	178mm x 100mm x 155mm 7-3/16 x 4-7/16 x 6-2/16 inch
(with Sleeve)	182mm x 112mm x 153mm 7-3/16 x 4-7/16 x 6 inch
Operational temperature range	-10°C to +60°C
Weight	Main unit 1.7 kg 3.8 lb

Quieting sensitivity	10.2dBf
DIN S/N 46dB	1.13μV / 75Ohms
Frequency response (±3.0dB)	30Hz - 15kHz
S/N (dB)	65dB (MONO)
Selectivity	Over 80dB (±400kHz)
Stereo separation	45dB (1kHz)

AM

Frequency Range (Frequency step)	530kHz - 1700kHz (10kHz)
Usable sensitivity	28dBμ

Video

Color system of external video input	NTSC/PAL
External video input level (Mini jacks)	1 Vp-p / 75 Ohms
External audio max input level (Mini jacks)	2 V / 25 kOhms
Video Input level (RCA jacks)	1 Vp-p / 75 Ohms
Video Output level (RCA jacks)	1 Vp-p / 75 Ohms
Audio Output level (Mini jacks)	0.9 V / 10 kOhms

Audio

Maximum Power Output (Front&Rear)	50Wx4
Typical Power Output (Front&Rear)	Full Bandwidth Power (at less than 1%THD) 22Wx4
Output frequency band	20 - 88,000Hz
Preout level (V)	5V / 10kOhms
Preout impedance (Ω)	≦ 300 Ohms
Speaker Impedance (Ω)	4-8 Ohms

General

Operating voltage	12V DC Car Battery
Maximum Current consumption	15A
Installation Dimensions WxHxD	178mm x 100mm x 155mm 7-3/16 x 4-7/16 x 6-2/16 inch
(with Sleeve)	182mm x 112mm x 153mm 7-3/16 x 4-7/16 x 6 inch
Operational temperature range	-10°C to +60°C
Weight	Main unit 1.7 kg 3.8 lb

Quieting sensitivity	10.2dBf
DIN S/N 46dB	1.13μV / 75Ohms
Frequency response (±3.0dB)	30Hz - 15kHz
S/N (dB)	65dB (MONO)
Selectivity	Over 80dB (±400kHz)
Stereo separation	45dB (1kHz)

AM

Frequency Range (Frequency step)	530kHz - 1700kHz (10kHz)
Usable sensitivity	28dBμ

Video

Color system of external video input	NTSC/PAL
External video input level (Mini jacks)	1 Vp-p / 75 Ohms
External audio max input level (Mini jacks)	2 V / 25 kOhms
Video Input level (RCA jacks)	1 Vp-p / 75 Ohms
Video Output level (RCA jacks)	1 Vp-p / 75 Ohms
Audio Output level (Mini jacks)	0.9 V / 10 kOhms

Audio

Maximum Power Output (Front&Rear)	50Wx4
Typical Power Output (Front&Rear)	Full Bandwidth Power (at less than 1%THD) 22Wx4
Output frequency band	20 - 88,000Hz
Preout level (V)	5V / 10kOhms
Preout impedance (Ω)	≦ 300 Ohms
Speaker Impedance (Ω)	4-8 Ohms

General

Operating voltage	12V DC Car Battery
Maximum Current consumption	15A
Installation Dimensions WxHxD	178mm x 100mm x 155mm 7-3/16 x 4-7/16 x 6-2/16 inch
(with Sleeve)	182mm x 112mm x 153mm 7-3/16 x 4-7/16 x 6 inch
Operational temperature range	-10°C to +60°C
Weight	Main unit 1.7 kg 3.8 lb