

FFAR121SS7



58.38" x 23.63" x 22.75" (H x W x D)

10.1 cu.ft. commercial all-refrigerator with stainless steel interior and exterior, digital thermostat, lock, and automatic defrost operation

Highlights:

Commercially listed to NSF-7 standards

Stainless steel construction inside and out ensures improved sanitation

Cantilevered shelving allows endless storage configurations to meet your needs

Product Features:

Commercially approved	ETL-S listed to ANSI-NSF Standard 7	
Stainless steel exterior	Door, cabinet, and kickplate feature complete stainless steel construction for lasting durability	
Stainless steel interior	Full construction on interior walls and floor ensures improved sanitation	
Digital thermostat	Electronic controls for more precise temperature management, with temperature readout and controls externally located for added convenience	
Cantilevered shelves	Adjustable chrome shelves can be arranged in virtually any configuration for flexible storage	
Factory installed lock	Keyed lock for secure interior	
Hospital grade cord with 'green dot' plug	Secure three-pronged cord for added unit safety	
Flat door liner	Allows you to store larger trays inside	
Automatic defrost	Reduced maintenance with auto defrost system	

 \checkmark





FFAR121SS7 Specifications:

Overview	
Height of Cabinet	58.38" (148 cm)
Width	23.63" (60 cm)
Depth	22.75" (58 cm)
Depth with Handle	24.63" (63 cm)
Depth with door at 90°	45.0" (114 cm)
Capacity	10.1 cu.ft. (286 L)
Defrost Type	Automatic
Door	Stainless Steel
Cabinet	Stainless Steel
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S
Amps	1.7
Voltage/Frequency	115 V AC/60 Hz
Weight	145.0 lbs. (66 kg)
Shipping Weight	150.0 lbs. (68 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
Refrigerator Features	
Door Swing	RHD
Reversible	Yes
Shelf Type	Chrome
Shelf Qty	4
Adjustable Shelves	Yes
Thermostat Type	Digital
Fan Type	Interior
Refrigerant Type	R600a
Refrigerant Amount	1.66oz.
High Side PSI	270.0
Low Side PSI	105.0
Interior Light	Yes
Temperature Range	2º to 6ºC
Dimensions	
Interior Height	50.25" (128 cm)
Interior Width	19.63" (50 cm)
Interior Depth	16.75" (43 cm)
Compressor Step Height	4.5" (11 cm)

Compressor Step Width	19.63" (50 cm)
Compressor Step Depth	4.5" (11 cm)

