

## Specifications

Description: Integrated Powered Loudspeaker system with Phono Preamp and Bluetooth compatible wireless Transmitter and Receiver.

<b>SPINPLAY</b>	
Turntable	Belt Drive with end-of-record Auto-Stop
Motor	Electronically governed DC
Tonearm	8.9" Statically balanced aluminum
Platter	12" cast-aluminum with damped silicone mat
Anti-Skating	Yes, adjustable
Phono Cartridge	Audio Technica AT3600L
Tracking Force	Preset @ 3g, manually adjustable. 2.5 - 3.5g recommended
Stylus	.6 Mil Conical
Replacement Styli	AT N3600LC (Conical), AT N3600LE (Elliptical)
Inputs	Phono (internal), Line (Aux), Optical Digital, Bluetooth, USB Flash Drive
Line Input Impedance	10kOhm
Optical Input Resolution	up to 24Bit/96kHz
USB File Format	MP3, WMA, WAV
Headphone Output	120mW @ 16 Ohms
Line Output	2V RMS
USB Power	5VDC/300MA
Power Input	100-250V AC / 50-60Hz / 1.5A
Amplifier Type	Dual Direct Drive Class-D
Tweeters	Two 3/4" silk dome
Woofers	Two 1.75" x 4" oval
Woofers Amplifier Power	20W/Ch. (40Hz - 2.5kHz)
Tweeter Amplifier Power	15W/Ch. (2.5kHz - 20kHz)
Enclosure Type	Reflex Vented braced MDF
Frequency Range	60Hz - 20kHz
Dimensions W x H x D (inch)	18" x 13.5" x 6.75"
Dimensions W x H x D (mm)	458mm x 343mm x 172mm
Weight	20.5Lb / 9.3kG

Andover Audio subscribes to a program of continuous improvement. As a result, some product features and characteristics may change without prior notice.