


KEY FEATURES

- Extensive Range of Heat Outputs: Available in models ranging from 2000W to 6000W
- ▶ Timeless Design: Showcases a stylish honeycomb mesh front with a high-temperature, corrosion-resistant coating and durable stainless-steel construction. Available in black and white finishes ensuring suitability for all environments
- Versatile Mounting Options: Supports wall, ceiling, and recessed installations, providing versatility to suit various space requirements
- Directional Heating: Adjustable bracket system allows for precise heat direction, optimizing comfort for specific seating or lounge areas


COLOR OPTIONS




Black




DIMENSIONS





MOUNTING OPTIONS







Ceiling Mounted

Flush Mounted







SPECIFICATIONS

PRODUCT NUMBER BLACK WHITE	WATTAGE	HEAT AREA	WEIGHT	RATED CURRENT*	MINIMUM FLOOR CLEARANCE	APPROVAL CERTIFICATION	IP RATING	CONTROL OPTIONS
BH0420030 (Black Only)	2000W	65ft²	19.8lbs.	220 - 240V/8.3A	WALL 72" CEILING 96"	INTERTEK ETL / cETL 4005951	IPX4	Affinity On/Off Affinity Dimmer Manual Wall Switch
BH0420038(Black Only) BH0420031 (Black Only)	3000W	100ft ²	22lbs.	208V/14.42A 220-240V/12.5A				
BH0420034 BH0420037 BH0420032 BH0420012 BH0420042 BH0420044	4000W	130ft²	19.8lbs.	208V/19.23A 220-240V/16.6A 277V14.44A				
BH0420035 BH0420036 BH0420033 BH0420013 BH0420043 BH0420045	6000W	160ft ²	22lbs.	208V/28.85A 220-240V/25A 277V/21.66A				


CLEARANCES

INCLUDED MOUNT






MOUNTING ACCESSORIES



BRACKET (INCLUDED)



CEILING RECESS

