Specifications

Digital Input	COAXIAL & OPTICAL	PCM 16-24Bit /44.1kHz, 48kHz, 88.2kHz, 96kHz, 176.4kHz, 192kHz MQA or MQA Studio stream DSD 2.82MHz, 3.07MHz(DoP)
	IIS LVDS	PCM 16-32Bit /44.1kHz, 48kHz, 88.2kHz, 96kHz, 176.4kHz, 192kHz, 352.8kHz, 384kHz, 705.6kHz, 768kHz DSD 2.82MHz, 3.07MHz, 5.64MHz, 6.14MHz, 11.29MHz, 12.29MHz (DoP) DSD 2.82MHz, 3.07MHz, 5.64MHz, 6.14MHz, 11.29MHz, 12.29MHz, 22.58MHz, 24.58MHz, 45.16MHz，49.15MHz (Native)
	USB Audio	PCM 16-24Bit /44.1kHz, 48kHz, 88.2kHz, 96kHz, 176.4kHz, 192kHz, 352.8kHz, 384kHz, 705.6kHz, 768kHz MQA 16-24Bit /44.1kHz, 48kHz, 88.2kHz, 96kHz, 176.4kHz, 192kHz, 352.8kHz, 384kHz MQA or MQA Studio stream DSD 2.82MHz, 5.64MHz, 11.29MHz (DoP) DSD 2.82MHz, 3.07MHz, 5.64MHz, 6.14MHz, 11.29MHz, 12.29MHz, 22.58MHz, 24.58MHz (Native)
Digital Output	IIS LVDS	PCM 16-32Bit /44.1kHz, 48kHz, 88.2kHz, 96kHz, 176.4kHz, 192kHz, 352.8kHz, 384kHz, 705.6kHz, 768kHz DSD 2.82MHz, 3.07MHz, 5.64MHz, 6.14MHz, 11.29MHz, 12.29MHz, 22.58MHz, 24.58MHz, 45.16MHz，49.15MHz (Native)
Aux Input	XLR	Input Impedance: 40kΩ SNR: 118dB A-weighting THD+N:<0.00026%@1k, <0.00030%@20Hz-20kHz Frequency Response: 20Hz-20kHz ±0.3 -3dB@46kHz Crosstalk: >-135dB Max Input Level: 4.9VRMS
	RCA	Input Impedance: 20kΩ SNR: 110dB A-weighting THD+N:<0.00060%@1k, <0.00100%@20Hz-20kHz Frequency Response: 20Hz-20kHz ±0.3 -3dB@46kHz Crosstalk: >-125dB Max Input Level: 2.35VRMS
	Phono	MM Mode Frequency Response: RIAA Input Impedance: 47kΩ/100pF GAIN: +45dB MC Mode Frequency Response: RIAA Input Impedance: 100Ω GAIN: +65dB
Line Output	XLR	Output Impedance： 20Ω Output Level: 5VRMS Fixed SNR: 131dB A-weighting THD+N:<0.000068%@1k, <0.000075%@20Hz-20kHz Frequency Response: 20Hz-20kHz ±0.05 -3dB@85kHz Crosstalk : >-150dB
Pre Output	XLR	Output Impedance： 40Ω Output Level: 0~16VRMS Adjustable GAIN：+10dB SNR: 131dB A-weighting THD+N:<0.000068%@1k, <0.000075%@20Hz-20kHz

		Frequency Response: 20Hz-20kHz ±0.05 -3dB@85kHz
		Crosstalk : >-150dB
	RCA	Output Impedance： 16Ω
		Output Level:0~8VRMS Adjustable
		GAIN：+10dB
		SNR: 127dB A-weighting
		THD+N:<0.000076%@1k, <0.000085%@20Hz-20kHz
		Frequency Response: 20Hz-20kHz ±0.08 -3dB@83kHz
		Channel Crosstalk : >-139dB
Network	LAN	10/100/1000 Mbps
	SFP	10/100/1000 Mbps
USB	USB 3.0 *2	The USB port provides a maximum power of 5V/1.5A.
		The USB port works with devices which conform to the USB mass storage standard and supports FAT, FAT32, exFAT, and NTFS file formats, but is not guaranteed to be compatible with all storage devices.
External Clock Input		10MHz / 50Ω / Sine wave or square wave input
Trigger	Trigger in	DC 6-12V <10mA
	Trigger out	DC 12V/50mA MAX
Storage Extension		M.2 2280 NVMe PCIe SSD slot x1
		The maximum power specification provided by the SSD slot is DC 3.3V 3A.
MA Player	Controller app	MA Remote App
	Local Playback	Format Supported：MP3 , WMA , WAV , AIF, AIFC, AIFF, AAC, FLAC, OGG, APE, ALAC, M4A, DSF, DFF, CUE
		PCM 16-24Bit/44.1kHz, 48kHz, 88.2kHz, 96kHz, 176.4kHz, 192kHz, 352.8kHz, 384kHz, 705.6kHz, 768kHz
		MQA 16-24Bit /44.1kHz, 48kHz, 88.2kHz, 96kHz, 176.4kHz, 192kHz, 352.8kHz, 384kHz MQA or MQA Studio stream
		DSD 2.82MHz, 3.07MHz, 5.64MHz, 6.14MHz, 11.29MHz, 12.29MHz, 22.58MHz, 24.58MHz
	Roon Ready	PCM 16-24Bit/44.1kHz, 48kHz, 88.2kHz, 96kHz, 176.4kHz, 192kHz, 352.8kHz, 384kHz, 705.6kHz, 768kHz
		MQA 16-24Bit /44.1kHz, 48kHz, 88.2kHz, 96kHz, 176.4kHz, 192kHz, 352.8kHz, 384kHz MQA or MQA Studio stream
		DSD 2.82MHz, 3.07MHz, 5.64MHz, 6.14MHz, 11.29MHz, 12.29MHz, 22.58MHz
	AirPlay 2	The audio specs depend on the service provider
	DLNA/UPnP	The audio specs depend on the service provider
	TIDAL Connect	The audio specs depend on the service provider
	Qobuz Connect	The audio specs depend on the service provider
	Spotify Connect	The audio specs depend on the service provider
	vTuner	The audio specs depend on the service provider
	Radio Paradise	The audio specs depend on the service provider
Power Specs	Power Voltage	AC 100V-120V 50/60Hz or AC 220V-240V 50/60Hz Factory fixed
	Standby Power Consumption	< 5W
	Maximum Power Consumption	< 60W

Weight & size	Weight	14.6kg (32.2 pounds)
	Dimensions	Width: 430 mm (16.93 inches)
		Depth: 353 mm (13.90 inches)
		Height: 106 mm (4.17 inches)
Accessory		RM4B remote control x 1
		Power cable x 1
		User manual x 1
		Warranty card x 1