

1224DWR • 24" Solid Refrigerator Drawers • 1000 Series









INTEGRATED SOLID

PERFORMANCE

- Volume of 5.4 cu ft holds up to 98 bottles (12 oz) or 150 cans (12 oz)
- Digital Touch Pad Control
- Temperature range: 34°F 45°F
- Passive cooling system

INTERIOR/EXTERIOR

- Black interior is illuminated with LED lighting
- Equipped with 2 full-extension robust stainless drawers
- Standard commercial stainless steel handle is interchangeable with professional handle accessory
- The lower drawer is large enough to fit 2 one-gallon containers with additional space for more storage

INTEGRATION

- Unit is designed to be built-in or can be freestanding with the freestanding accessory kit
- Integrated model requires 3/4" custom door panel (panels not supplied by U-Line)
- Four independently adjustable leveling legs provide a precise undercounter fit
- Available in the following finishes: Stainless or Integrated

MODEL DETAILS

Model	Voltage/Hz	Door Swing	Finish	Shipping Weight
U-1224DWRS-00B	115 / 60	Drawers	Stainless Solid	142 lb
U-1224DWRINT-00B	115 / 60	Drawers	Integrated Solid	134 lb

ACCESSORIES

Model	Description	Finish	Shipping Weight
80-54462-00	Professional Drawer Handle, 1 1/4" Diameter	Stainless	2 lb
U-FSK-B	Freestanding Kit	Black	3 lb
80-54362-00	Top Drawer Slide and Divide Bin Organizer 1k	N/A	3 lb


FEATURES & BENEFITS




1000 Series • 24" Solid Refrigerator Drawers • 1224DWR

DIMENSIONS

Dimensions shown apply to all finishes, including Integrated (INT) models with $3/4^{\prime\prime}$ integrated panel/frame installed.



CABINET CUT-OUT



SPECIFICATIONS

Model	1224DWR	
Amps: Running	1.2	
Capacity: Bottle (12 oz)	98	
Capacity: Can (12 oz)	150	
Capacity: Volume (cu ft)	5.4	
Control Type	Digital Touch Pad	
Dimensions: Product Depth	23 ½" / 591 mm	
Dimensions: Product Height	34 ½" / 867 mm	
Dimensions: Product Width	24" / 610 mm	
Energy Consumption: Avg. Per Year	305 kWh	
ENERGY STAR	No	
Panel Height	15" / 381 mm	
Panel Thickness	³ / ₄ " / 20 mm	
Panel Type	Solid Panel	
Panel Width	23 ³ / ₄ " / 603 mm	
Product Weight: Max	132 lb	
Refrigerant Type	R600a	
Sabbath (Star K Certified)	Yes	
Temperature Range	34°F - 45°F	

INSTALLATION NOTES

Cutout includes the additional 1/4" width overall to ensure proper installation.

No additional clearance around sides, top or rear of unit is needed for ventilation.

COOLING SYSTEM



ELECTRICAL REQUIREMENTS

This unit requires a grounded, polarized 115 VAC, 60 Hz, 15 A power supply (normal household current).







Warranty

Please visit u-line.com to view this model's User Guide & Service Manual. All Specifications are subject to change without notice.