

General Features

	P-XRW1202DB	P-XRW1202WB	P-XRW1002DB	P-XRW1002WB
Subwoofer Specification	12" Oversized Cone Subwoofer	12" Oversized Cone Subwoofer	10" Oversized Cone Subwoofer	10" Oversized Cone Subwoofer
Peak Power	2000W	2000W	1300W	1300W
RMS Power	400W	400W	300W	300W
Impedance	2ΩSingle Voice Coil	2ΩSingle Voice Coil	2ΩSingle Voice Coil	2ΩSingle Voice Coil
Frequency Response	33Hz -300Hz	33Hz -300Hz	31Hz -300Hz	31Hz -300Hz
Features	Dual Ventilation System	Dual Ventilation System	Dual Ventilation System	Dual Ventilation System
	Stress-Free Damper	Stress-Free Damper	Stress-Free Damper	Stress-Free Damper
	8AWG Push Terminals	8AWG Push Terminals	8AWG Push Terminals	8AWG Push Terminals
	Rubber Magnet Cover	Rubber Magnet Cover	Rubber Magnet Cover	Rubber Magnet Cover
Enclosure Specifications	Low Profile Sealed Down-Firing Design	Sealed Wedge Design	Low Profile Sealed Down-Firing Design	Sealed Wedge Design
	Black Carpeted 3/4" MDF Enclosure	Black Carpeted 3/4" MDF Enclosure	Black Carpeted 3/4" MDF Enclosure	Black Carpeted 3/4" MDF Enclosure
	Acoustic Damping Material	Acoustic Damping Material	Acoustic Damping Material	Acoustic Damping Material
	Dimensions: 9"(H) x 16"(W) x 22"(L)	Dimensions: 14"(H) x 14"(W) x 20"(L)	Dimensions:8.5"(H) x 15"(W) x 20"(L)	Dimensions: 12-5/8"(H) x 12-3/4"(W) x 18"(L)