

UM15N



Colour range
Body



Blue
grey – BG



Antique
white – AW



White – WH



Blue – MB



Stainless
steel – SS



Graphite
matt – MG



Glossy
black – BK



Burgundy
red – BU



Emerald
green – EG



Optional RAL – RA



Brass – G



Copper – P



Chrome – C



Burnished – B

Finishes
Knobs, handles, frames

Optional solid door version


optional +

Order code: add letter "Q" before the "N" letter

Available ovens

Electric oven	
Primary oven:	Secondary oven:
UOV 80 E3 TFT S	UOV 60 E3 TFT
Maximum input:	Maximum input:
3.7 kW	3.5 kW

Configurations



Electric oven

UM15FDNS3

Brass/Copper/Chrome/Burnished

Fuel requirements


Natural gas / Liquid propane

Voltage: 240 Volts

Amps: 30

**Insufficient amperage may lower heating performance when multiple functions are being used at the same time*

Consumption

 Double ring Dual burner 20000 btu/h / 900 btu/h	 Double ring burner 16500 btu/h / 6200 btu/h	 Griddle 10500 btu/h / 2000 btu/h + 7000 btu/h / 1400 btu/h	 Oval burner 10500 btu/h / 3100 btu/h	 Big burner 10500 btu/h / 2000 btu/h	 Small burner 7000 btu/h / 1400 btu/h
--	--	---	---	--	---

Complements & accessories

Hood	UAM150	Ladle holder panel	AM4-150
------	--------	--------------------	---------

Technical drawing & dimensions

