



Product: 36 Inch Wall Mount Range Hood

Model Number: HRH3607

BLOWER RATING

BLOWER RATINGS	CFM	(dBA)
Low	330 CFM	41.5
Medium	420 CFM	47.5
High	600 CFM	56

PRODUCT DIMENSIONS

Range Hood Size	36
Product Width (in)	35 3/8
Product Depth (in)	19 3/4
Product Height (in)	33 1/2 - 55
Duct Size (in)	6
Duct Shape	Round



FEATURES & BENEFITS

- + Multiple Fan Speeds** - 3 fan speeds allow for easy adjustment between high, medium and low suction
- + LED Lighting** - Two 3.5-watt LED lights to illuminate your cooking area and save energy
- + Quiet 56dB Operation** - Quiet operation keeps noise level at a maximum 56 decibels
- + Convertible** - Vent out or recirculating (ductless) option with carbon filters (not included)
- + Commercial-style Baffle Filter** - Large, commercial-style 430 grade stainless steel baffle filter maximizes airflow and minimizes grease while the hood is in operation.
- + Touch Control with Digital Display** - Features touch control with integrated backlit digital display that shows clock and a reminder to clean filters
- + 600 CFM of Suction** - 600 CFM of suction effectively removes odors, smoke, grease and moisture from your cooking area
- + Stainless Steel Finish** - Stainless steel finish offers modern design aesthetic and is built to withstand high heat, grease, oil and steam
- + Remote Control** - Remote control allows for adjusting fan speed and lighting from anywhere in the kitchen
- + Duct Cover Included:** The stainless steel duct cover matches the linear styling of the THOR kitchen professional 36 Inch vent hood and extends the height of the hood for 10 foot ceilings

TECHNICAL DETAILS

Lighting	LED light x 2
Noise level (Max.)	56 dB
Power	120V
Frequency	60HZ
Amperage	5A
Filter type	430SS Baffle filter
Blower type	Internal
Control type	no auto shut off No delayed shut off 12 hour timer
Accessories	FT05 Charcoal Filter / Not Included
Color/Finish	Stainless steel

WARRANTY: 2 YEARS ON PARTS AND LABOR



INSTALLATION & SPEC

INSTALLTION DRILLING AND LINING

1. Draw a vertical line on the wall where the hood will be installed, up to the ceiling or as high as needed.
2. Draw a horizontal line 28-30 inches above an electric cooktop or 30-32 inches above a gas cooktop.
3. Place chimney mounting brackets on the wall as shown about 1"(27mm) from the ceiling or upper limit aligning the centre(notch)with the vertical reference line.

