

COMMERCIAL  
THROUGH RETAIL

COIN SLIDE  
STACKED  
DRYERS



Product		Stacked Dryer Tall
Color		White
Capacity - lb (kg)		18 (8.2) ea
Cylinder Volume - cu.ft. (liters)		7.0 (198) ea
Motor (Thermal Protected) - HP		0.33
Type of Gas (Gas Models Only)		Factory Equipped Natural
Available Cycles		Normal, Perm Press, Delicate, No Heat
Air Outlet Diameter - in		4
Exhaust Airflow - cfm (liters/sec)		220 (105)
Electrical Requirements (v/Hz/Ph-Amp)	*Electric	208-240/60/1-30 Amp
	Gas	120/60/1-15 Amp
Heating Element	Electric	5350W, 240V / 4750W, 208V
	Gas	25,000 Btu
Net Weight - lb (kg)		270 (122)
Shipping Weight - lb (kg)		277 (126)
Shipping Dimensions Approx. - in	Width	33
	Depth	30
	Height	80
Agency Approvals	Electric	cULus
	Gas	cCSAus
Model No.		SSESXAGS173TW01, SSGSXAGS113TW01
Required Coin Kits (sold separately)		Coin Box Model #: CK124 (2 required)

Dimensions	Width - in	Height - in	Depth - in	Floor to Door Opening - in	Door Swing - in
Stacked Dryer - Tall	26.875	78.17	28	15.44	23.5

**Note** (not supplied): Each stacked dryer pocket requires its own power cord.

For Commercial Use Only

\* Electric dryers are dual rated for 208-240V applications. Using dryer in 208V will reduce the wattage output. An optional kit (61928) can be used to field convert the unit for 4750 output at 208V.  
Gas dryers can be field converted for operation on LP gas with optional 458P3 conversion kit.

For additional accessories and warranty, please refer to the price list.